

# EBK 5 GA automatic

WATER BOILERS PRODUCT-NO.: 074287

#### Choose a technology with maximum transparency

Best prospects for hot water on the spot. With this automatic water heater, you can watch the water reach the required temperature, as the body is made of heat-resistant glass. Combined with a suitable tap, the appliance looks great in your kitchen.



### Experience convenience automatically

The appliance brings water to the boil with ease and conveniently shuts itself off automatically when the preferred temperature is reached. This much convenience ensures that you never lose your good mood in the kitchen.



EBK 5 G automatic Product-No.: 074286

#### The main features

Cold, warm or boiling water from one draw-off point

With boiling point detection and automatic shutdown, immediate re-boiling is possible

Variable temperature adjustment

Elegant, heat-resistant glass container

Straightforward installation thanks to standard plug

With standard chrome tap







Туре	EBK 5 G automatic	EBK 5 GA automatic
Part no.	074286	074287

# Technical data

Connected load       2 kW       2 kW         Power supply       1/N/PE       1/N/PE         Rated voltage       230 V       230 V         Frequency       50 Hz       50 Hz         Nominal capacity       5 l       5 l         Tap       Twin lever fill and drain valve       Three lever tap and drain valve         Type       non-pressurised       non-pressurised         Cylinder material       Glass       Glass         Colour       white       white         Temperature selection       100 °C       100 °C         Width       245 mm       245 mm         Depth       242 mm       242 mm         Capacity up to       5,0 l       5,0 l         Weight       4.10 kg       4.10 kg         Tap surface       plastic-coated       chrome plated			
Rated voltage230 V230 VFrequency50 Hz50 HzNominal capacity5 l5 lTapTwin lever fill and drain valveThree lever tap and drain valveTypenon-pressurisednon-pressurisedCylinder materialGlassGlassColourwhitewhiteTemperature selection100 °C100 °CWidth245 mm245 mmDepth242 mm242 mmCapacity up to5,0 l5,0 lWeight4.10 kg4.10 kg	Connected load	2 kW	2 kW
Frequency 50 Hz 50 Hz  Nominal capacity 5 l 5 l  Tap Twin lever fill and drain valve rough r	Power supply	1/N/PE	1/N/PE
Nominal capacity 5 l 5 l  Tap Twin lever fill and drain valve  Type non-pressurised non-pressurised  Cylinder material Glass Glass  Colour white white  Temperature selection 100 °C 100 °C  Width 245 mm 245 mm  Depth 242 mm  Capacity up to 5,0 l 5,0 l  Weight 4.10 kg 4.10 kg	Rated voltage	230 V	230 V
Tap Twin lever fill and drain valve  Type non-pressurised non-pressurised  Cylinder material Glass Glass  Colour white white  Temperature selection 100 °C 100 °C  Width 245 mm 245 mm  Depth 242 mm  Capacity up to 5,0 l 5,0 l  Weight 4.10 kg 4.10 kg	Frequency	50 Hz	50 Hz
Type non-pressurised non-pressurised Cylinder material Glass Glass Colour white white Temperature selection 100 °C 100 °C Width 245 mm 245 mm Depth 242 mm Capacity up to 5,0 l 5,0 l Weight 4.10 kg 4.10 kg	Nominal capacity	5 l	5 l
Cylinder material Glass Glass  Colour white white  Temperature selection 100 °C 100 °C  Width 245 mm 245 mm  Depth 242 mm  Capacity up to 5,0 l 5,0 l  Weight 4.10 kg 4.10 kg	Тар		Three lever tap
Colour White White Temperature selection 100 °C 100 °C Width 245 mm 245 mm Depth 242 mm 242 mm Capacity up to 5,0 l 5,0 l Weight 4.10 kg 4.10 kg	Туре	non-pressurised	non-pressurised
Temperature selection 100 °C 100 °C  Width 245 mm 245 mm  Depth 242 mm 242 mm  Capacity up to 5,0 l 5,0 l  Weight 4.10 kg 4.10 kg	Cylinder material	Glass	Glass
Width       245 mm       245 mm         Depth       242 mm       242 mm         Capacity up to       5,0 l       5,0 l         Weight       4.10 kg       4.10 kg	Colour	white	white
Depth         242 mm         242 mm           Capacity up to         5,0 l         5,0 l           Weight         4.10 kg         4.10 kg	Temperature selection	100 °C	100 °C
Capacity up to         5,0 l         5,0 l           Weight         4.10 kg         4.10 kg	Width	245 mm	245 mm
Weight 4.10 kg 4.10 kg	Depth	242 mm	242 mm
	Capacity up to	5,0 l	5,0 l
Tap surface plastic-coated chrome plated	Weight	4.10 kg	4.10 kg
	Tap surface	plastic-coated	chrome plated



## **Contact information**

You have questions? We appreciate to help you: Call +49 5531 - 7020 Write an email to info@stiebel-eltron.com

#### Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.