

SRC R UP

TEMPERATURE CONTROLLER

PRODUCT-NO.: 234420

Flush mounting receiver, with strain relief for wireless room temperature control in combination with a wireless room temperature controller. Operation of the radiant heater, natural stone heater or storage heater, ideal for retrofitting. In the event of wireless connection being lost, runtime is set to 30 % to prevent frost damage.



The main features

Breaking capacity from 30 °C room temperature: 7.5 A

Breaking capacity up to 30 °C room temperature: 11 A

For consumers in safety category I and II

Installation on unfinished walls (deep junction box recommended)

Emergency mode if wireless connection is lost



Type	SRC C digital	SRC R AP	SRC R UP
Part no.	234417	234421	234420
Height	110 mm	83 mm	85 mm
Depth	26 mm	25 mm	42 mm
Width	110 mm	78 mm	81 mm
Colour	White (similar to RAL 9010)	White (similar to RAL 9010)	White (similar to RAL 9010)

Technical data

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.