

BHE 75 Plus

BATHROOM RADIATOR

PRODUCT-NO.: 238713

Bathroom radiators: Added value with added enjoyment.

The bathroom radiators of the BHE Plus series combine functionality with design. The electrical connection offers the advantage that even when your central heating system is off (for example in summer), both room and towels can be pleasantly warmed when necessary. The user friendly position of the programming unit enables easy access to temperature control. The comfort functions of the integral controller highlight the efficiency and high quality features of the bathroom radiator.



The main features

Electric bathroom radiator

750 W heating output

May also be connected to the hot water heating network

Factory-filled with process medium for purely electrical operation

Quick room air heating

Premium design with circular pipes

Controls with backlit LCD

With infinitely variable temperature selection

Protection: IP 24



Type	BHE 50 Plus	BHE 75 Plus	BHE 100 Plus
Part no.	239141	238713	238714

Heating output

Rated heating output P_{nom}	0,50 kW	0,75 kW	1,00 kW
Minimum heat output (standard value) P_{min}	0,00 kW	0,00 kW	0,00 kW
Maximum continuous heating output $P_{max,c}$	0,50 kW	0,75 kW	1,00 kW

Auxiliary power consumption

D heating output $e_{l_{max}}$	0,00 kW	0,00 kW	0,00 kW
Heat output $e_{l_{min}}$	0,00 kW	0,00 kW	0,00 kW
Dby mode $e_{l_{SB}}$	0,00 kW	0,00 kW	0,00 kW

Type of heating output/room temperature control

Single stage heating output, no room temperature control	-	-	-
Two or more manually adjustable stages, no room temperature control	-	-	-
Room temperature control with mechanical thermostat	-	-	-
With electronic room temperature control	-	-	-
Electronic room temperature control and time of day control	-	-	-
Electronic room temperature control and day of week control	x	x	x

Other control options

Room temperature control with occupancy detection	-	-	-
Room temperature control with open window detection	-	-	-
With remote control option	-	-	-
With adaptive control for start of heating	x	x	x
With restricted operating times	-	-	-
With black bulb sensor	-	-	-



Type	BHE 175 T Plus
Part no.	238715

Heating output

Rated heating output P_{nom}	1,75 kW
Minimum heat output (standard value) P_{min}	0,00 kW
Maximum continuous heating output $P_{max,c}$	1,75 kW

Auxiliary power consumption

D heating output $e_{l_{max}}$	0,00 kW
Heat output $e_{l_{min}}$	0,00 kW
Dby mode $e_{l_{SB}}$	0,00 kW

Type of heating output/room temperature control

Single stage heating output, no room temperature control	-
Two or more manually adjustable stages, no room temperature control	-
Room temperature control with mechanical thermostat	-
With electronic room temperature control	-
Electronic room temperature control and time of day control	-
Electronic room temperature control and day of week control	X

Other control options

Room temperature control with occupancy detection	-
Room temperature control with open window detection	-
With remote control option	-
With adaptive control for start of heating	X
With restricted operating times	-
With black bulb sensor	-

Depth including wall mounting bracket

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.