


CND 150

CONVECTOR HEATERS

PRODUCT-NO.: 234815

APPLICATION: Wall mounted heat wave convector as an efficient heating system for spring and autumn and for additional heat demand in the living space, bathroom, hallway or in utility rooms. The two integrated heating systems for radiant heating and convection heating ensure a pleasant and cosy room temperature. The elegant and minimalist design blends into any modern setting.



EQUIPMENT / CONVENIENCE: Designer radiator with 2 heating systems and precise electronic control with intelligent energy saving functions. When the window is open, the appliance automatically switches to frost protection mode; the motion sensor recognises when nobody is left inside the room and automatically lowers the set room temperature. The 7-day timer offers 3 preset time programs that can be individually adjusted to suit current requirements.

INSTALLATION / SERVICE: Straightforward and stable wall mounting by one person only. The appliance is connected using a permanent power supply. Maintenance free.

SAFETY: Integral high limit safety cut-out and omnipolar ON/OFF switch.

The main features

Modern and high grade design

Controls with backlit LCD

7-day timer, frost protection and open window detection

ON/OFF switch and overheating protection



Type	CND 75	CND 100	CND 150
Part no.	234813	234814	234815

Heating output

Rated heating output P_{nom}	0,8 kW	1,0 kW	1,5 kW
Minimum heat output (standard value) P_{min}	0,0 kW	0,0 kW	0,0 kW
Maximum continuous heating output $P_{max,c}$	0,8 kW	1,0 kW	1,5 kW

Auxiliary power consumption

D heating output $e_{l_{max}}$	0,000 kW	0,000 kW	0,000 kW
Heat output $e_{l_{min}}$	0,000 kW	0,000 kW	0,000 kW
Dby mode $e_{l_{SB}}$	0,000 kW	0,000 kW	0,000 kW

Type of heating output/room temperature control

Single stage heating output, no room temperature control	-	-	-
Two or more manually adjustable stages, no room temperature control	-	-	-
Room temperature control with mechanical thermostat	-	-	-
With electronic room temperature control	-	-	-
Electronic room temperature control and time of day control	-	-	-
Electronic room temperature control and day of week control	x	x	x

Other control options

Room temperature control with occupancy detection	x	x	x
Room temperature control with open window detection	x	x	x
With remote control option	-	-	-
With adaptive control for start of heating	-	-	-
With restricted operating times	-	-	-
With black bulb sensor	-	-	-



Type	CND 200
Part no.	234816

Heating output

Rated heating output P_{nom}	2,0 kW
Minimum heat output (standard value) P_{min}	0,0 kW
Maximum continuous heating output $P_{max,c}$	2,0 kW

Auxiliary power consumption

D heating output $e_{l_{max}}$	0,000 kW
Heat output $e_{l_{min}}$	0,000 kW
Dby mode $e_{l_{SB}}$	0,000 kW

Type of heating output/room temperature control

Single stage heating output, no room temperature control	-
Two or more manually adjustable stages, no room temperature control	-
Room temperature control with mechanical thermostat	-
With electronic room temperature control	-
Electronic room temperature control and time of day control	-
Electronic room temperature control and day of week control	x

Other control options

Room temperature control with occupancy detection	x
Room temperature control with open window detection	x
With remote control option	-
With adaptive control for start of heating	-
With restricted operating times	-
With black bulb sensor	-

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.