


# CND 200

CONVECTOR HEATERS

PRODUCT-NO.: 234816

## CND duo convector – heat in both its forms.

With its two integral heating systems for radiant heating and convection heating, the CND wall mounted duo convector ensures a pleasant and cosy room temperature. The elegant minimalist design of the wall mounted convector blends into any modern setting.



The duo convector presence detection feature automatically reduces the room temperature once a room is vacated. If a window is opened, the heating also switches off automatically. The integral controller allows the comfort temperature to be controlled precisely and can be used to set the temperature via the weekly timer.

## The main features

Wall mounted duo convector – ideal as a booster heater or interim heater in spring/autumn

Even, pleasant room air heating

2000 W connected load

Modern and high grade design

Controls with backlit LCD

7-day timer, frost protection and open window detection

Electronic control unit with presence detection

ON/OFF switch and overheating protection

Permanent connection with pilot control cable



Type	CND 75	CND 100	CND 150
<b>Part no.</b>	234813	234814	234815

## Heating output

<b>Rated heating output <math>P_{nom}</math></b>	0,8 kW	1 kW	1,5 kW
<b>Minimum heat output (standard value) <math>P_{min}</math></b>	0 kW	0 kW	0 kW
<b>Maximum continuous heating output <math>P_{max,c}</math></b>	0,8 kW	1 kW	1,5 kW

## Auxiliary power consumption

<b>D heating output <math>e_{l_{max}}</math></b>	0,000 kW	0,000 kW	0,000 kW
<b>Heat output <math>e_{l_{min}}</math></b>	0,000 kW	0,000 kW	0,000 kW
<b>Dby mode <math>e_{l_{SB}}</math></b>	0,000 kW	0,000 kW	0,000 kW

## Type of heating output/room temperature control

<b>Single stage heating output, no room temperature control</b>	-	-	-
<b>Two or more manually adjustable stages, no room temperature control</b>	-	-	-
<b>Room temperature control with mechanical thermostat</b>	-	-	-
<b>With electronic room temperature control</b>	-	-	-
<b>Electronic room temperature control and time of day control</b>	-	-	-
<b>Electronic room temperature control and day of week control</b>	x	x	x

## Other control options

<b>Room temperature control with occupancy detection</b>	x	x	x
<b>Room temperature control with open window detection</b>	x	x	x
<b>With remote control option</b>	-	-	-
<b>With adaptive control for start of heating</b>	-	-	-
<b>With restricted operating times</b>	-	-	-
<b>With black bulb sensor</b>	-	-	-



Type	CND 200
Part no.	234816

#### Heating output

Rated heating output $P_{nom}$	2 kW
Minimum heat output (standard value) $P_{min}$	0 kW
Maximum continuous heating output $P_{max,c}$	2 kW

#### Auxiliary power consumption

D heating output $e_{l_{max}}$	0,000 kW
Heat output $e_{l_{min}}$	0,000 kW
Dby mode $e_{l_{SB}}$	0,000 kW

#### Type of heating output/room temperature control

Single stage heating output, no room temperature control	-
Two or more manually adjustable stages, no room temperature control	-
Room temperature control with mechanical thermostat	-
With electronic room temperature control	-
Electronic room temperature control and time of day control	-
Electronic room temperature control and day of week control	x

#### Other control options

Room temperature control with occupancy detection	x
Room temperature control with open window detection	x
With remote control option	-
With adaptive control for start of heating	-
With restricted operating times	-
With black bulb sensor	-

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.