

# CNS 100 Trend M

CONVECTORS

PRODUCT-NO.: 203640

Do you want pleasant temperatures in very specific places in your home? In addition to your central heating? Then this practical wall mounted convector is the heater for you. Its slimline design makes it very easy to integrate.

The slimline appliance is very robust and can therefore withstand even the chaos and commotion of everyday life. An integrated frost protection function precludes heating system failures due to low temperatures.



## The main features

Compact wall mounted convector, ideal as an auxiliary heater or interim heater in spring/autumn

---

Extremely slimline design

---

Mechanical temperature controller

---

Safety through overheating protection

---

Robust design

---

Frost protection setting



Type	CNS 50 Trend M	CNS 100 Trend M	CNS 150 Trend M
Part no.	203638	203640	203641

## Heating output

Rated heating output P <sub>nom</sub>	0.50 kW	1.00 kW	1.50 kW
Minimum heating output (standard value) P <sub>min</sub>	0.00 kW	0.00 kW	0.00 kW
Maximum continuous heating output P <sub>max,c</sub>	0.50 kW	1.00 kW	1.50 kW

## Auxiliary power consumption

H rated heating output e <sub>Hmax</sub>	0.00 kW	0.00 kW	0.00 kW
H minimum heating output e <sub>Hmin</sub>	0.00 kW	0.00 kW	0.00 kW
Dby mode e <sub>SB</sub>	0.00 kW	0.00 kW	0.00 kW

## Type of heating output/room temperature control

Single stage heating output, no room temperature control	-	-	-
Two or more manual stages, no room temperature control	-	-	-
With mechanic thermostat room temperature control	x	x	x
With electronic room temperature control	-	-	-
Electronic room temperature control plus day timer	-	-	-
Electronic room temperature control plus week timer	-	-	-

## Other control options

Room temperature control, with presence detection	-	-	-
Room temperature control, with open window detection	-	-	-
With distance control option	-	-	-
With adaptive start control	-	-	-
With working time limitation	-	-	-
With black bulb sensor	-	-	-



Type	CNS 200 Trend M	CNS 250 Trend M	CNS 300 Trend M
Part no.	203642	203643	203644

## Heating output

Rated heating output P <sub>nom</sub>	2.00 kW	2.50 kW	3.00 kW
Minimum heating output (standard value) P <sub>min</sub>	0.00 kW	0.00 kW	0.00 kW
Maximum continuous heating output P <sub>max,c</sub>	2.00 kW	2.50 kW	3.00 kW

## Auxiliary power consumption

H rated heating output e <sub>Hmax</sub>	0.00 kW	0.00 kW	0.00 kW
H minimum heating output e <sub>Hmin</sub>	0.00 kW	0.00 kW	0.00 kW
Dby mode e <sub>SB</sub>	0.00 kW	0.00 kW	0.00 kW

## Type of heating output/room temperature control

Single stage heating output, no room temperature control	-	-	-
Two or more manual stages, no room temperature control	-	-	-
With mechanic thermostat room temperature control	x	x	x
With electronic room temperature control	-	-	-
Electronic room temperature control plus day timer	-	-	-
Electronic room temperature control plus week timer	-	-	-

## Other control options

Room temperature control, with presence detection	-	-	-
Room temperature control, with open window detection	-	-	-
With distance control option	-	-	-
With adaptive start control	-	-	-
With working time limitation	-	-	-
With black bulb sensor	-	-	-

Depth including wall mounting bracket

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.