


# CNS 200 F

CONVECTOR HEATERS

PRODUCT-NO.: 229794

The CNS-F may be used as a freestanding appliance wherever heat is required quickly. To operate this convector heater as a freestanding appliance, simply attach the feet with fitted castors supplied. With this appliance you'll be playing it safe, as it immediately shuts down if it accidentally gets knocked over. The integral thermal link also protects it from overheating. These very narrow appliances are robust and splashproof.



## The main features

Including feet with castors

---

Splashproof to IP 24

---

High safety during operation, due to integral pendulum switch

---

ON/OFF switch

---

Power cable for a permanent connection



Type	CNS 100 F	CNS 200 F	CNS 250 F
Part no.	229790	229794	229795
Connected load	1,0 kW	2,0 kW	2,5 kW
Width	445 mm	740 mm	890 mm
Depth	305 mm	305 mm	305 mm
Height	555 mm	555 mm	555 mm

## Technical data

Power supply	1/N ~ 220-240 V	1/N ~ 220-240 V	1/N ~ 230 V
Frequency	50/- Hz	50/- Hz	50/- Hz
Rated voltage	230 V	230 V	230 V
Rated current	4,3 A	8,7 A	10,9 A
Setting range	6-30 °C	6-30 °C	6-30 °C
IP-Rating	IP24	IP24	IP24
Protection class	II	II	II
Weight	4,9 kg	7,3 kg	8,6 kg
Colour	alpine white	alpine white	alpine white

Dimensions including castor feet

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.