

CON 5 Premium

CONVECTORS

PRODUCT-NO.: 237830

Precision heating with style

With this direct heater, you enhance your room in two ways. The appliance not only provides pleasant heat, but also blends in perfectly with your interior décor thanks to its high quality design. So you don't have to choose between warmth and style.

Flexible heat control

The wall mounted convector also plays to its strengths when it comes to convenience. Use the weekly timer to set a precise temperature for several days, or adjust the temperature spontaneously at the touch of a button for anything from ten minutes to two hours. When you air the room, the appliance switches off automatically.

The main features

Wall mounted convector – ideal as an auxiliary heater or interim heater in spring/autumn

Even, quiet, air heating


High quality design with an aluminium front

Operating controls with illuminated LCD screen

Weekly timer, 120-minute timer, frost protection and open window detection

Control unit with self-learning capability: automatic calculation of the preheat time in timer mode

ON/OFF switch and overheating protection



CON 10 Premium

Product-No.: 237831




CON 15 Premium

Product-No.: 237832




CON 20 Premium

Product-No.: 237833



CON 30 Premium

Product-No.: 237834



Type	CON 5 Premium	CON 10 Premium	CON 15 Premium
Part no.	237830	237831	237832

Technical data

Power supply	1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V
Rated voltage	230 V	230 V	230 V
Rated current	2,2 A	4,3 A	6,5 A
Connected load	0,5 kW	1,0 kW	1,5 kW
IP rating	IP24	IP24	IP24
Protection class	I	I	I
Colour	alpine white	alpine white	alpine white
Setting range	5-30 °C	5-30 °C	5-30 °C
Height	470 mm	470 mm	470 mm
Width	345 mm	470 mm	625 mm
Depth	126 mm	126 mm	126 mm
Weight	4.30 kg	5.90 kg	7.50 kg



Type	CON 20 Premium	CON 30 Premium
Part no.	237833	237834

Technical data

Power supply	1/N/PE ~ 230 V	1/N/PE ~ 230 V
Rated voltage	230 V	230 V
Rated current	8,7 A	13 A
Connected load	2 kW	3 kW
IP rating	IP24	IP24
Protection class	I	I
Colour	alpine white	alpine white
Setting range	5-30 °C	5-30 °C
Height	470 mm	470 mm
Width	780 mm	1090 mm
Depth	126 mm	126 mm
Weight	9.30 kg	12.60 kg

Depth including wall mounting bracket

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.