

IA receiver

OUTDOOR RADIANT HEATER

PRODUCT-NO.: 233875

Wireless receiver for individual output reduction on infrared radiant heaters. Offers 4-stage control (0 %, 50 %, 66 % and 100 % of output). The receiver is installed in the connecting cable using a Hirschmann connector and plugs. The appliance is switched via separately available remote controls.



The main features

Wireless receiver with bidirectional function

May be controlled in 4 stages (0 %, 50 %, 66 % and 100 %)

Remote control available as an accessory

Pulse pack control enables saving electricity in proportion



Type	IA 2054 extreme	IA 2024 outdoor	IA receiver
Part no.	233882	233889	233875
Connected load	2 kW	2 kW	0 - 2 kW
Height	100 mm	145 mm	300 mm
Width	610 mm	480 mm	105 mm
Depth	80 mm	145 mm	30 mm

Technical data

Power connection	1/N/PE~230 V	1/N/PE~230 V	1/N/PE~230 V
Frequency	50/- Hz	50/- Hz	50/- Hz
Rated voltage	230 V		230 V
Rated current	8.5 A	8.5 A	0 - 8,5 A
Type of installation	horizontal/vertical	Horizontal	Finished walls
IP-Rating	IP54	IP24	IP54
Protection class	I	I	I
Weight	2,5 kg	2,5 kg	0,800 kg
Colour	silver	white	black



Type	IA remote control
Part no.	234728
Connected load	
Height	120 mm
Width	51 mm
Depth	26 mm
Technical data	
Power connection	miscellaneous
Frequency	
Rated voltage	3 V
Rated current	
Type of installation	miscellaneous
IP-Rating	IP20
Protection class	
Weight	0,120 kg
Colour	white

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.