

# RHB 300

RADIANT HEATER

PRODUCT-NO.: 234422

The frameless and very slim design with the minimalist glass surface fits into any modern environment. Our radiant heaters emit a special form of heat which is perceived as particularly pleasant. The all-round bezel on the back means that the wall mounting bracket and power supply are no longer visible post installation.



## The main features

300 W heating output

---

Black glass surface

---

Pleasant radiated heat

---

The clear design language highlights high grade interior appeal

---

Ideal for use as a booster or auxiliary heater

---

Optional installation vertically and horizontally

---

Straightforward and quick installation by a single person



Type	RHB 300	RHB 500	RHB 700
Part no.	234422	234423	234424

## Heating output

Rated heating output $P_{nom}$	0,28 kW	0,50 kW	0,70 kW
Minimum heat output (standard value) $P_{min}$	0,00 kW	0,00 kW	0,00 kW
Maximum continuous heating output $P_{max,c}$	0,28 kW	0,50 kW	0,70 kW

## Auxiliary power consumption

D heating output $e_{l_{max}}$	0,00 kW	0,00 kW	0,00 kW
Heat output $e_{l_{min}}$	0,00 kW	0,00 kW	0,00 kW
Dby mode $e_{l_{SB}}$	0,00 kW	0,00 kW	0,00 kW

## Type of heating output/room temperature control

Single stage heating output, no room temperature control	-	-	-
Two or more manually adjustable stages, no room temperature control	-	-	-
Room temperature control with mechanical thermostat	-	-	-
With electronic room temperature control	-	-	-
Electronic room temperature control and time of day control	-	-	-
Electronic room temperature control and day of week control	x	x	x

## Other control options

Room temperature control with occupancy detection	-	-	-
Room temperature control with open window detection	-	-	-
With remote control option	-	-	-
With adaptive control for start of heating	x	x	x
With restricted operating times	-	-	-
With black bulb sensor	-	-	-



Type	RHB 900
Part no.	234425

#### Heating output

Rated heating output $P_{nom}$	0,90 kW
Minimum heat output (standard value) $P_{min}$	0,00 kW
Maximum continuous heating output $P_{max,c}$	0,90 kW

#### Auxiliary power consumption

D heating output $e_{l_{max}}$	0,00 kW
Heat output $e_{l_{min}}$	0,00 kW
Dby mode $e_{l_{SB}}$	0,00 kW

#### Type of heating output/room temperature control

Single stage heating output, no room temperature control	-
Two or more manually adjustable stages, no room temperature control	-
Room temperature control with mechanical thermostat	-
With electronic room temperature control	-
Electronic room temperature control and time of day control	-
Electronic room temperature control and day of week control	x

#### Other control options

Room temperature control with occupancy detection	-
Room temperature control with open window detection	-
With remote control option	-
With adaptive control for start of heating	x
With restricted operating times	-
With black bulb sensor	-

Installation and commissioning of the equipment is only permitted in connection with external room temperature controllers that fulfil the following functions: Electronic room temperature control with weekday control and adaptive control of when heating starts. These requirements are fulfilled by the STIEBEL ELTRON room temperature controllers RTU-TC and SRC C digital. Failure to observe these requirements will result in a loss of the CE designation.

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.