

CK 20 Trend

RAPID HEATER

PRODUCT-NO.: 234918

This rapid heater generates the required heat directly. It not only saves on space but is also easy to use. One power outlet is all that this electrical appliance needs.

The temperature can be very easily regulated thanks to the convenient positioning of the controls. Furthermore, the appliance only needs a small recess in which to get on with its task.



The main features

Wall mounted rapid heater – ideal as a supplementary heater or interim heater in spring/autumn

Quick room air heating

Maximum safety thanks to three-stage overheating protection

Small footprint

Ideal for the bathroom



Type	CK 20 Trend
Part no.	234918

Heating output

Rated heating output P _{nom}	2.00 kW
Minimum heating output (standard value) P _{min}	0.00 kW
Maximum continuous heating output P _{max,c}	2.00 kW

Auxiliary power consumption

H rated heating output e _{lmax}	0.00 kW
H minimum heating output e _{lmin}	0.00 kW
Dby mode e _{lSB}	0.00 kW

Type of heating output/room temperature control

Single stage heating output, no room temperature control	-
Two or more manual stages, no room temperature control	-
With mechanic thermostat room temperature control	x
With electronic room temperature control	-
Electronic room temperature control plus day timer	-
Electronic room temperature control plus week timer	-

Other control options

Room temperature control, with presence detection	-
Room temperature control, with open window detection	-
With distance control option	-
With adaptive start control	-
With working time limitation	-
With black bulb sensor	-

Depth including wall mounting bracket

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.