

ETC 340 M

ETC-M

PRODUCT-NO.: 182062

Storage heater ETC has a particularly slimline design so you can fit it in anywhere. Pleasant heat is primarily radiated via the surface with a low convective component. There are versions with manual and automatic charging. These appliances are equipped with simple controls at the front.



The main features

Compact dimensions

High proportion of radiant heat

Heat transfer without fan

Manual or automatic charging

Easy to install



Type	ETC 085 M	ETC 170 M	ETC 250 M
Part no.	182059	182060	182061
Rated connected load	0,85 kW	1,7 kW	2,55 kW
Height	700 mm	700 mm	700 mm
Depth	170 mm	170 mm	170 mm
Width	355 mm	585 mm	815 mm

Technical data

Power supply	1/N/PE ~ 220-240 V	1/N/PE ~ 220-240 V	1/N/PE ~ 220-240 V
Frequency	50/- Hz	50/- Hz	50/- Hz
Rated voltage	~230 V	~230 V	~230 V
Rated current	3,7 A	7,4 A	11,1 A
Number of stone packs	2	4	6
Weight (incl. blocks)	43,5 kg	81 kg	119,5 kg
Colour	pure white, RAL 9010	pure white, RAL 9010	pure white, RAL 9010



Type	ETC 340 M
Part no.	182062
Rated connected load	3,4 kW
Height	700 mm
Depth	170 mm
Width	1045 mm

Technical data

Power supply	1/N/PE ~ 220-240 V
Frequency	50/- Hz
Rated voltage	~230 V
Rated current	14,8 A
Number of stone packs	8
Weight (incl. blocks)	158 kg
Colour	pure white, RAL 9010

Depth including 31 mm wall spacer

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.