


SHP-F 300 Premium






DHW HEAT PUMPS

PRODUCT-NO.: 238631

Obligatory supplies

Article	Part no.	Type	Description
	074370	ZH 1	Safety assembly ZH 1 for sealed unvented electric floorstanding cylinders pressure reducing valve DMV/ZH1, may be retrofitted. Brass casing, G 3/4 connections. Response pressure, safety relief valve: 0,6 MPa, Connection: G 1 A

Additional supplies

Article	Part no.	Type	Description
	074374	SV 3/4-6	Diaphragm safety valve with brass casing, response pressure 0.6 Mpa (6 bar).
	073864	<u>ZTA 3/4</u>	Thermostatic valve, Water connection: G 3/4 A
	234505	<u>AWG 160 R</u>	Thermally insulating EPS wall outlet incl. weather grille with drip edge, Max. air flow rate: 350 m ³ /h, External pipe diameter: 200 mm, Connection diameter: 160 mm, Max. air volume: 350 m ³ /h
	074370	ZH 1	Safety assembly ZH 1 for sealed unvented electric floorstanding cylinders pressure reducing valve DMV/ZH1, may be retrofitted. Brass casing, G 3/4 connections. Response pressure, safety relief valve: 0,6 MPa, Connection: G 1 A
	074371	DMV / ZH 1	Special pressure reducing valve G 1 as supplement to ZH 1, if the static pressure at the installation location exceeds 0.48 MPa (4.8 bar). Brass. Connection 3/4 inch.



236899

LUS 221/301

Air diverter hood set

Contact information

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.