

DCE 11/13 RC

PRODUCT-NO.: 230771

Stay in control – even remotely

This appliance is designed with such compact dimensions that it can be invisibly concealed in a kitchen base unit. It can then be controlled quite simply with a wireless remote control. This allows you to conveniently make settings, such as temperature changes, from a distance. It doesn't get much easier than that!



The main features

Electronically controlled compact instantaneous water heater

Very good energy efficiency thanks to 3i technology

Convenient, accurate temperature settings

Two temperature memory buttons for quick temperature selection

Adjustable temperature limit as anti-scalding protection for children

With wireless remote control as standard

Exceptionally slimline, compact design



Type	DCE 11/13 RC
Part no.	230771

Technical data

Rated voltage	400 V
Rated voltage 1	380 V
Rated voltage 2	400 V
Rated voltage 3	415 V
Rated output	11.2/13.5 kW
Rated output 1	10.1/12.2 kW
Rated output 2	11.2/13.5 kW
Rated output 3	12.1/14.5 kW
Rated current	18.7/19.5 A
Rated current 1	17.8/18.5 A
Rated current 2	18.7/19.5 A
Rated current 3	19.4/20.2 A
Fuse protection	16/20 A
Fuse protection 1	16/20 A
Fuse protection 2	16/20 A
Fuse protection 3	20/20 A
Frequency	50/60 Hz
Frequency 1	50/60 Hz
Frequency 2	50/60 Hz
Frequency 3	50/- Hz
Phases	3/PE
Resistivity $\rho_{15} \geq$ (at $\vartheta_{cold} \leq 25$ °C and 380 V)	900 Ω cm

Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25$ °C and 400 V)	900 Ω cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25$ °C and 415 V)	900 Ω cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 55$ °C and 380 V)	1100 Ω cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 55$ °C and 400 V)	1100 Ω cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 55$ °C and 415 V)	1100 Ω cm
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25$ °C and 380 V)	1111 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25$ °C and 400 V)	1111 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25$ °C and 415 V)	1111 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 55$ °C and 380 V)	909 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 55$ °C and 400 V)	909 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 55$ °C and 415 V)	909 $\mu\text{S}/\text{cm}$
IP rating	IP 24
Temperature setting	20-60 °C
Colour	white
ON	>2.5 l/min
Height	293 mm
Width	188 mm
Depth	85 mm
Weight	2.40 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.