

DCE-C 6/8 Trend

COMPACT INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 238148

The main features

Electronically controlled compact instantaneous water heater with 2i technology for excellent energy efficiency and constant accurate temperature delivery

Temperature set permanently to 55°C

Quick PROFI-RAPID installation

Selectable output can be adjusted internally

High quality design | Made in Germany

Suitable for reheating preheated water up to 55 °C (maximum inlet temperature 70 °C)





Type	DCE-C 6/8 Trend	DCE-C 10/12 Trend
Part no.	238148	238149
Rated output	6,6/8,7 kW	11,0/13,1 kW
Height	372 mm	372 mm
Width	217 mm	217 mm
Depth	98 mm	98 mm

Technical data

Rated voltage 1	220 V	220 V
Rated output 1	6,0/8,0 kW	10,0/12,0 kW
Rated current 1	27,3/36,4 A	45,5/54,5 A
Fuse 1	30/40 A	50/60 A
Frequency 1	50/60 Hz	50/60 Hz
Rated voltage 2	230 V	230 V
Rated output 2	6,6/8,7 kW	11,0/13,1 kW
Rated current 2	28,5/38,0 A	47,8/57,0 A
Fuse 2	30/40 A	50/60 A
Frequency 2	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE
Temperature adjustment	55 °C	55 °C
Specific resistance $\rho_{15} \geq$	1100 Ω cm	1100 Ω cm
Specific conductivity $\sigma_{15} \leq$	910 μ S/cm	910 μ S/cm
Energy efficiency class	A	A
Colour	white	white
IP-Rating	IP25	IP25
Weight	2,5 kg	2,5 kg

Expected to be available from June 2019

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.