

DCE 11/13 H

COMPACT INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 232792

Electronically controlled compact instantaneous water heater with 3i technology. Accurate temperature delivery up to the maximum output. Very rapid DHW heating and high temperature stability due to bare wire heating system. Selectable connected load 11 kW or 13.5 kW. With power cable as standard. DHW heating from 20 - 60 °C, accurate temperature adjustment via rotary temperature selector on the appliance.



The main features

Electronically controlled instantaneous water heater

Exceptionally flat compact design

Selectable connected load 11 kW or 13.5 kW

Particularly convenient and energy efficient due to electronic output control

Precise temperature selection from 20 °C to 60 °C

Anti-scalding protection

Oversink installation



Type	DCE 11/13 H
Part no.	232792
Rated output	11,2/13,5 kW
Height	293 mm
Width	188 mm
Depth	85 mm

Technical data

Rated voltage 1	380 V
Rated output 1	10,1/12,2 kW
Rated current 1	17,8/18,5 A
Fuse 1	16/20 A
Frequency 1	50/60 Hz
Rated voltage 2	400 V
Rated output 2	11,2/13,5 kW
Rated current 2	18,7/19,5 A
Fuse 2	16/20 A
Frequency 2	50/60 Hz
Rated voltage 3	415 V
Rated output 3	12,1/14,5 kW
Rated current 3	19,4/20,2 A
Fuse 3	20/20 A
Frequency 3	50/- Hz
Phases	3/PE
Temperature adjustment	20-60 °C
Specific resistance $\rho_{15} \geq$ (at $\vartheta_{cold} \leq 25$ °C and 380 V)	900 Ω cm

Specific resistance $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25$ °C and 400 V)	900 Ω cm
Specific resistance $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25$ °C and 415 V)	900 Ω cm
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25$ °C and 380 V)	1111 $\mu\text{S}/\text{cm}$
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25$ °C and 400 V)	1111 $\mu\text{S}/\text{cm}$
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25$ °C and 415 V)	1111 $\mu\text{S}/\text{cm}$
Specific resistance $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 55$ °C and 380 V)	1100 Ω cm
Specific resistance $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 55$ °C and 400 V)	1100 Ω cm
Specific resistance $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 55$ °C and 415 V)	1100 Ω cm
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 55$ °C and 380 V)	909 $\mu\text{S}/\text{cm}$
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 55$ °C and 400 V)	909 $\mu\text{S}/\text{cm}$
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 55$ °C and 415 V)	909 $\mu\text{S}/\text{cm}$
Energy efficiency class	A
Colour	white
IP-Rating	IP24
Weight	2,20 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.