

DHC 6

COMPACT INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 073480

The DHC series of hydraulically controlled, pressure-tested and compact instantaneous water heaters have been specially developed for single phase power supply. Installed close to the draw-off point – either shower or sink – the DHC provides the required volume of hot water at the right temperature.



The main features

3.0 - 6.0 kW (subject to model)

Multi-functional unit for one or more draw-off points

No scalding or overheating thanks to automatic switch-OFF

Precise temperature convenience through infinitely variable adjustment

Also for use in low pressure areas

Splashproof to IP 25

Easy and quick installation

Easy operation



Type	DHA 4/8 L	DHC 4	DHC 6
Part no.	073716	073715	073480
Rated output	8.8 kW	4,4 kW	6.6 kW
Depth	105 mm	104 mm	104 mm
Height	362 mm	360 mm	360 mm
Width	200 mm	200 mm	200 mm

Technical data

Rated voltage 1	220 V	220 V	220 V
Rated output 1	8,0/6,0/4,0 kW	4,0 kW	6,0 kW
Rated current 1	36,3/27,4/18,3 A	18,1 A	27,2 A
Fuse 1	40/32/20 A	20 A	30 A
Rated voltage 2	230 V	230 V	230 V
Rated output 2	8,8/6,6/4,4 kW	4,4 kW	6,6 kW
Rated current 2	38,2/28,7/19,1 A	19,1 A	28,6 A
Fuse 2	40/32/20 A	20 A	30 A
Rated voltage 3	240 V	240 V	240 V
Rated output 3	9,6/7,2/4,8 kW	4,8 kW	7,2 kW
Rated current 3	40/29,9/20,0 A	20,8 A	30,0 A
Fuse 3	40/32/20 A	20 A	30 A
Phases	1/N/PE	1/N/PE	1/N/PE
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Water connection	G 1/2	G 3/8 A	G 3/8 A
Energy efficiency class	A	A	A
Colour	white	white	white
IP-Rating	IP24	IP24	IP24

Weight

2,60 kg

2,10 kg

2,40 kg



Type	DHC 8	DHC 6 U
Part no.	073481	073479
Rated output	8.8 kW	6,6 kW
Depth	104 mm	104 mm
Height	360 mm	360 mm
Width	200 mm	200 mm

Technical data

Rated voltage 1	220 V	220 V
Rated output 1	8,0 kW	6,0 kW
Rated current 1	36,3 A	27,2 A
Fuse 1	40 A	30 A
Rated voltage 2	230 V	230 V
Rated output 2	8,8 kW	6,6 kW
Rated current 2	38,2 A	28,6 A
Fuse 2	40 A	30 A
Rated voltage 3	240 V	240 V
Rated output 3	9,6 kW	7,2 kW
Rated current 3	40,0 A	30,0 A
Fuse 3	40 A	30 A
Phases	1/N/PE	1/N/PE
Frequency	50/60 Hz	50/60 Hz
Water connection	G 3/8 A	G 3/8 A
Energy efficiency class	A	A
Colour	white	white
IP-Rating	IP24	IP24

Weight

2,40 kg

2,40 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.