

DHF 18 C

PRODUCT-NO.: 074303

Engage a top performer The power to impress: this compact instantaneous water heater has two output levels – and you don't even have to actively choose between them. The appliance switches automatically to the right level, depending on the flow rate. Your current needs therefore set the tone for this hydraulically controlled model.



The main features

Installation possible with commercially available taps

For soft water areas

Wide output range

Ideal for installation situations with concealed connections



Type	DHF 13 C	DHF 15 C	DHF 18 C
Part no.	074301	074302	074303

Technical data

Rated voltage	400 V	400 V	400 V
Rated output	13.2 kW	15 kW	18 kW
Rated current	20 A	22 A	26 A
Fuse protection	20 A	25 A	32 A
Frequency	50 Hz	50 Hz	50 Hz
Phases	3/PE	3/PE	3/PE
Power supply	3/PE	3/PE	3/PE
Water connection	G 1/2 A	G 1/2 A	G 1/2 A
ON	>3.0 l/min	>3.0 l/min	>3.9 l/min
IP rating	IP 24	IP 24	IP 24
Colour	white	white	white
Height	370 mm	370 mm	370 mm
Width	220 mm	220 mm	220 mm
Depth	130 mm	130 mm	130 mm
Weight	4.10 kg	4.10 kg	4.10 kg



Type	DHF 21 C
Part no.	074304
Technical data	
Rated voltage	400 V
Rated output	20,5 kW
Rated current	29,6 A
Fuse protection	32 A
Frequency	50 Hz
Phases	3/PE
Power supply	3/PE
Water connection	G 1/2 A
ON	>4.4 l/min
IP rating	IP 24
Colour	white
Height	370 mm
Width	220 mm
Depth	130 mm
Weight	4.10 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.