

DHF 12 C1

COMPACT INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 182137

The DHF instantaneous water heater is a valid alternative, if the installation situation, or the water conductivity make the use of an instantaneous water heater difficult. This hydraulically-controlled instantaneous water heater, with two-stage temperature selection, offers high output in the tightest of spaces. The control valve automatically compensates for most pressure fluctuations in the water supply.



The main features

Hydraulically controlled instantaneous water heater

Two-stage temperature and output selection

Compact dimensions

Option to install in the shower area

For soft water areas



Type	DHF 12 C1	DHF 13 C	DHF 13 C3
Part no.	182137	074301	185708
Rated output	13,2 kW	13.2 kW	13,2 kW
Height	370 mm	370 mm	370 mm
Width	220 mm	220 mm	220 mm
Depth	130 mm	130 mm	130 mm

Technical data

Rated output	13,2 kW	13.2 kW	13,2 kW
Power supply	1/N/PE	3/PE	3/PE
Rated current	57,3 A	19.5 A	33 A
Fuse protection	60 A	20 A	35 A
Rated voltage	220/230 V	400 V	230 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Water connection	G 1/2 A	G 1/2 A	G 1/2 A
Energy efficiency class	B	B	B
Colour	white	white	white
IP-Rating	IP24	IP24	IP24
Weight	4,10 kg	4,10 kg	4,10 kg



Type	DHF 15 C	DHF 18 C	DHF 21 C
Part no.	074302	074303	074304
Rated output	15 kW	18 kW	21 kW
Height	370 mm	370 mm	370 mm
Width	220 mm	220 mm	220 mm
Depth	130 mm	130 mm	130 mm

Technical data

Rated output	15 kW	18 kW	21 kW
Power supply	3/PE	3/PE	3/PE
Rated current	21.7 A	26 A	30.4 A
Fuse protection	25 A	32 A	32 A
Rated voltage	400 V	400 V	400 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Water connection	G 1/2 A	G 1/2 A	G 1/2 A
Energy efficiency class	B	B	B
Colour	white	white	white
IP-Rating	IP24	IP24	IP24
Weight	4,10 kg	4,10 kg	4,10 kg



Type	DHF 24 C
Part no.	074305
Rated output	24 kW
Height	370 mm
Width	220 mm
Depth	130 mm

Technical data

Rated output	24 kW
Power supply	3/PE
Rated current	34,2 A
Fuse protection	35 A
Rated voltage	400 V
Frequency	50/60 Hz
Water connection	G 1/2 A
Energy efficiency class	B
Colour	white
IP-Rating	IP24
Weight	4,10 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.