

# DEL 27 Plus

PRODUCT-NO.: 236740

Equip your home perfectly for anything

This series with 3i technology leads the way in terms of high DHW convenience. With its wide range of features, such as a backlit multifunction display, temperature memory, childproofing and ECO mode, this appliance boosts convenience levels for you in a multitude of ways.



Save energy at the press of a button

The energy and water saving ECO mode limits the maximum flow rate. You benefit from a constant supply of hot water, even at low inlet temperatures. And you reduce your water consumption without compromising on convenience.

Enjoy incredible ease of use

With the optional wireless remote control, you can very conveniently control your instantaneous water heater from a distance.

## The main features

Electronically controlled instantaneous water heater

---

Accurate temperature delivery up to the appliance's output limit thanks to 3i technology

---

Sufficient hot water for multiple draw-off points

---

Particularly economical operation with ECO mode

---

Backlit multifunction display with output values

---

Individual memory buttons for setting preferred temperatures

---

Adjustable temperature limit as anti-scalding protection for children

---

Can be combined with a wireless remote control



| Type     | DEL 18/21/24 Plus | DEL 27 Plus |
|----------|-------------------|-------------|
| Part no. | 236739            | 236740      |

## Technical data

|                                 |                  |                 |
|---------------------------------|------------------|-----------------|
| Rated voltage                   | 400 V            | 400 V           |
| Rated voltage 1                 | 380 V            | 380 V           |
| Rated voltage 2                 | 400 V            | 400 V           |
| Rated output                    | 18/21/24 kW      | 27 kW           |
| Rated output 1                  | 16.2/19/21.7 kW  | 24.4 kW         |
| Rated output 2                  | 18/21/24 kW      | 27 kW           |
| Rated current                   | 29/31/35 A       | 39 A            |
| Rated current 1                 | 27.6/29.5/33.3 A | 37.1 A          |
| Rated current 2                 | 29/31/35 A       | 39 A            |
| Fuse protection                 | 32/32/35 A       | 40 A            |
| Fuse protection 1               | 32/32/35 A       | 40 A            |
| Fuse protection 2               | 32/32/35 A       | 40 A            |
| Frequency                       | 50/60 Hz         | 50/- Hz         |
| Frequency 1                     | 50/60 Hz         | 50/- Hz         |
| Frequency 2                     | 50/60 Hz         | 50/- Hz         |
| Phases                          | 3/PE             | 3/PE            |
| Resistivity $\rho_{15} \geq$    | 900 $\Omega$ cm  | 900 $\Omega$ cm |
| Conductivity $\sigma_{15} \leq$ | 1111 $\mu$ S/cm  | 1111 $\mu$ S/cm |
| IP rating                       | IP 25            | IP 25           |
| Temperature setting             | 20-60 °C         | 20-60 °C        |
| Colour                          | white            | white           |
| ON                              | >2.5 l/min       | >2,5 l/min      |

|               |         |         |
|---------------|---------|---------|
| <b>Height</b> | 466 mm  | 466 mm  |
| <b>Width</b>  | 225 mm  | 225 mm  |
| <b>Depth</b>  | 116 mm  | 116 mm  |
| <b>Weight</b> | 3.10 kg | 3.10 kg |

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.