

DEL 18/21/24 Plus

CONVENIENCE INSTANTANEOUS WATER
HEATER

PRODUCT-NO.: 236739

The main features

Electronically controlled instantaneous water heater

3i technology for accurate temperature delivery up to maximum output

Selectable output 18/21/24 kW in a single appliance

Temperature memory keys

Adjustable temperature limit for childproofing (anti-scalding protection)





Type	DEL 18/21/24 Plus	DEL 27 Plus
Part no.	236739	236740
Rated output	18/21/24 kW	27 kW
Height	466 mm	466 mm
Width	225 mm	225 mm
Depth	116 mm	116 mm

Technical data

Rated voltage 1	380 V	380 V
Rated output 1	16,2/19/21,7 kW	24,4 kW
Rated current 1	27,6/29,5/33,3 A	37,1 A
Fuse 1	32/32/35 A	40 A
Frequency 1	50/60 Hz	50/- Hz
Rated voltage 2	400 V	400 V
Rated output 2	18/21/24 kW	27 kW
Rated current 2	29/31/35 A	39 A
Fuse 2	32/32/35 A	40 A
Frequency 2	50/60 Hz	50/- Hz
Rated voltage 3	415 V	
Rated output 3	19,4/22,6/25,8 kW	
Rated current 3	30,1/32,2/36,3 A	
Fuse 3	32/32/40 A	
Frequency 3	50/- Hz	
Phases	3/PE	3/PE
Temperature adjustment	Off, 20-60 °C	Off, 20-60 °C
Specific conductivity $\sigma_{15 \leq}$ (at $\vartheta_{\text{cold}} \leq 25 \text{ °C}$)	1111 $\mu\text{S/cm}$	1111 $\mu\text{S/cm}$

Specific resistance $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^\circ\text{C}$)	900 Ω cm	900 Ω cm
Specific resistance $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 55 \text{ }^\circ\text{C}$ and 380 V)	900 Ω cm	900 Ω cm
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 55 \text{ }^\circ\text{C}$ and 380 V)	1111 $\mu\text{S}/\text{cm}$	1111 $\mu\text{S}/\text{cm}$
Specific resistance $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 55 \text{ }^\circ\text{C}$ and 400 V)	900 Ω cm	900 Ω cm
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 55 \text{ }^\circ\text{C}$ and 400 V)	1111 $\mu\text{S}/\text{cm}$	1111 $\mu\text{S}/\text{cm}$
Specific resistance $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 55 \text{ }^\circ\text{C}$ and 415 V)	900 Ω cm	900 Ω cm
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 55 \text{ }^\circ\text{C}$ and 415 V)	1111 $\mu\text{S}/\text{cm}$	1111 $\mu\text{S}/\text{cm}$
Energy efficiency class	A	A
IP-Rating	IP25	IP25
Colour	white	white
Weight	3,2 kg	3,2 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.