

## PEG 24

PRODUCT-NO.: 233997

Rely on a constant output This instantaneous water heater makes things particularly easy for you. The two-stage selection determines the temperature at which the water comes out of the tap. You can specify one of two temperatures using a rotary selector. Once set, you can rely on it completely. Carefree warm water Our appliance reliably maintains the selected temperature thanks to its electronic control system. In addition, it indicates when you are at risk of scalding. So there is nothing to stop you enjoying soothing warm water every single day.



### The main features

Maximum comfort thanks to electronic control

---

Consistent temperature delivery up to the maximum output

---

High energy efficiency – up to 30% savings possible compared with hydraulic instantaneous water heaters

---

Two-stage temperature setting with application symbols

---

Scale-resistant bare wire heating system



Type	PEG 13	PEG 18	PEG 21
Part no.	233994	233995	233996

## Technical data

Rated voltage	400 V	400 V	400 V
Rated voltage 1	380 V	380 V	380 V
Rated voltage 2	400 V	400 V	400 V
Rated output	13,5 kW	18 kW	21 kW
Rated output 1	12,2 kW	16.2 kW	19 kW
Rated output 2	13,5 kW	18 kW	21 kW
Rated current	19,5 A	26 A	31 A
Rated current 1	18,5 A	24.7 A	29.5 A
Rated current 2	19,5 A	26 A	31 A
Fuse protection	20 A	25 A	32 A
Fuse protection 1	20 A	25 A	32 A
Fuse protection 2	20 A	25 A	32 A
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 1	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 2	50/60 Hz	50/60 Hz	50/60 Hz
Phases	3/PE	3/PE	3/PE
Resistivity $\rho_{15} \geq$ (at $\vartheta_{cold} \leq 25$ °C and 380 V)	1100 $\Omega$ cm	1100 $\Omega$ cm	1100 $\Omega$ cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{cold} \leq 25$ °C and 400 V)	1100 $\Omega$ cm	1100 $\Omega$ cm	1100 $\Omega$ cm
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{cold} \leq 25$ °C and 380 V)	900 $\mu$ S/cm	900 $\mu$ S/cm	900 $\mu$ S/cm
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{cold} \leq 25$ °C and 400 V)	900 $\mu$ S/cm	900 $\mu$ S/cm	900 $\mu$ S/cm
ON	>3,0 l/min	>3.0 l/min	>3.0 l/min
Temperature setting	42 - 55 °C	42 - 55 °C	42 - 55 °C

<b>Colour</b>	white	white	white
<b>Height</b>	485 mm	485 mm	485 mm
<b>Width</b>	226 mm	226 mm	226 mm
<b>Depth</b>	93 mm	93 mm	93 mm
<b>Weight</b>	3.60 kg	3.60 kg	3.60 kg



Type	PEG 24
Part no.	233997

## Technical data

Rated voltage	400 V
Rated voltage 1	380 V
Rated voltage 2	400 V
Rated output	24 kW
Rated output 1	21.7 kW
Rated output 2	24 kW
Rated current	35 A
Rated current 1	33.3 A
Rated current 2	35 A
Fuse protection	35 A
Fuse protection 1	35 A
Fuse protection 2	35 A
Frequency	50/60 Hz
Frequency 1	50/60 Hz
Frequency 2	50/60 Hz
Phases	3/PE
Resistivity $\rho_{15} \geq$ (at $\vartheta_{cold} \leq 25$ °C and 380 V)	1100 $\Omega$ cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{cold} \leq 25$ °C and 400 V)	1100 $\Omega$ cm
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{cold} \leq 25$ °C and 380 V)	900 $\mu$ S/cm
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{cold} \leq 25$ °C and 400 V)	900 $\mu$ S/cm
ON	>3.0 l/min
Temperature setting	42 - 55 °C

<b>Colour</b>	white
<b>Height</b>	485 mm
<b>Width</b>	226 mm
<b>Depth</b>	93 mm
<b>Weight</b>	3.60 kg

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.