

# DHM 6 220

MINI INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 220815

## The main features

Hydraulically controlled mini instantaneous water heater for energy efficient and water saving supply of a single hand wash basin

Undersink installation

Can be operated with pressurised and non-pressurised taps

Special aerator with flow rate limiter for M 22 (fem.) and M 24 (male)

Instant hot water thanks to rapid and maintenance-free bare wire heating system

Quick PROFI-RAPID installation





Type	DHM 3	DHM 4	DHM 6
Part no.	220813	220814	185473
Rated output	3,53 kW	4,4 kW	5,7 kW
Height	143 mm	143 mm	143 mm
Width	190 mm	190 mm	190 mm
Depth	82 mm	82 mm	82 mm

## Technical data

Rated voltage 2	220 V	220 V	220 V
Rated output 2	3,2 kW	4,0 kW	5,2 kW
Rated current 2	14,5 A	18,2 A	23,6 A
Fuse 2	16 A	20 A	25 A
Frequency 2	50/60 Hz	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE	1/N/PE
Water connection	G 3/8 A	G 3/8 A	G 3/8 A
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25$ °C)	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$
Specific resistance $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25$ °C)	1100 $\Omega$ cm	1100 $\Omega$ cm	1100 $\Omega$ cm
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} > 25$ °C)	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$
Specific resistance $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} > 25$ °C)	1100 $\Omega$ cm	1100 $\Omega$ cm	1100 $\Omega$ cm
Energy efficiency class	A	A	A
Colour	white	white	white
IP-Rating	IP25	IP25	IP25
Weight	1,6 kg	1,6 kg	1,6 kg



Type	DHM 6 220	DHM 7
Part no.	220815	232789
Rated output	6,0 kW	6,5 kW
Height	143 mm	143 mm
Width	190 mm	190 mm
Depth	82 mm	82 mm

#### Technical data

Rated voltage 2	220 V	400 V
Rated output 2	6 kW	6,5 kW
Rated current 2	27,3 A	16,3 A
Fuse 2	32 A	20 A
Frequency 2	50 Hz	50/60 Hz
Phases	1/N/PE	2/PE
Water connection	G 3/8 A	G 3/8 A
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25$ °C)	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$
Specific resistance $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25$ °C)	1100 $\Omega$ cm	1100 $\Omega$ cm
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} > 25$ °C)	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$
Specific resistance $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} > 25$ °C)	1100 $\Omega$ cm	1100 $\Omega$ cm
Energy efficiency class	A	A
Colour	white	white
IP-Rating	IP25	IP25
Weight	1,5 kg	1,6 kg

**Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

**Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.