STIEBEL ELTRON

Technical datasheet

EIL 6 Plus

MINI INSTANTANEOUS WATER HEATERS

PRODUCT-NO.: 200140

The fastest way to enjoy hot waterDiscover all the options Are there places in your home where you only need hot water occasionally? Then this mini instantaneous water heater is the right solution for you. The water quickly gets up to temperature thanks to decentralised installation.

The main features

Suitable for undersink installation

Can be operated with pressure-tested or non-pressurised taps

Special aerator for perfect flow pattern

Mini instantaneous water heater with hydraulic control for small amounts of hot water available immediately

EIL 3 Plus
Product-No.: 200138

EIL 4 Plus
Product-No.: 200139

EIL 7 Plus
Product-No.: 200141

Type	EIL 3 Plus	EIL 4 Plus	EIL 6 Plus
Part no.	200138	200139	200140

Technical data

Rated voltage	230 V	230 V	230 V
Rated voltage 1	200 V	200 V	200 V
Rated voltage 2	220 V	220 V	220 V
Rated voltage 3	230 V	230 V	230 V
Rated voltage 4	240 V	240 V	240 V
Rated output	3,53 kW	4,4 kW	5,7 kW
Rated output 1	2,7 kW	3,3 kW	4,3 kW
Rated output 2	3,2 kW	4,0 kW	5,2 kW
Rated output 3	3,53 kW	4,4 kW	5,7 kW
Rated output 4	3,8 kW	4,8 kW	6,2 kW
Rated current	15,2 A	19,1 A	24,7 A
Rated current 1	13,3 A	16,7 A	21,6 A
Rated current 2	14,5 A	18,2 A	23,6 A
Rated current 3	15,2 A	19,1 A	24,7 A
Rated current 4	15,8 A	20 A	25,8 A
Fuse protection	16 A	20 A	25 A
Fuse protection 1	16 A	20 A	25 A
Fuse protection 2	16 A	20 A	25 A
Fuse protection 3	16 A	20 A	25 A
Fuse protection 4	16 A	20 A	32 A
Frequency	50/60 Hz	50/60 Hz	50/60 Hz

Frequency 1	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 2	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 3	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 4	50/60 Hz	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE	1/N/PE
Conductivity σ15 ≤	909 µS/cm	909 µS/cm	909 µS/cm
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C)	909 µS/cm	909 µS/cm	909 µS/cm
Conductivity σ15 ≤ (at ϑcold > 25 °C)	909 µS/cm	909 µS/cm	909 µS/cm
Resistivity ρ15 ≥	1100 Ω cm	1100 Ω cm	1100 Ω cm
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C)	1100 Ω cm	1100 Ω cm	1100 Ω cm
Resistivity ρ15 ≥ (at ϑcold > 25 °C)	1100 Ω cm	1100 Ω cm	1100 Ω cm
Height	143 mm	143 mm	143 mm
Width	190 mm	190 mm	190 mm
Depth	82 mm	82 mm	82 mm
Water connection	G 3/8 A	G 3/8 A	G 3/8 A
ON	> 1,6 l/min	> 2,0 l/min	> 2,6 l/min
IP rating	IP25	IP25	IP25
Colour	white	white	white
Weight	1.40 kg	1.40 kg	1.40 kg
Energy efficiency class	A	A	A

STIEBEL ELTRON

Technical datasheet

Type	EIL 7 Plus
Part no.	200141

Technical data

Rated voltage	400 V
Rated voltage 1	380 V
Rated voltage 2	400 V
Rated voltage 3	415 V
Rated voltage 4	
Rated output	6,5 kW
Rated output 1	5,9 kW
Rated output 2	6,5 kW
Rated output 3	7,0 kW
Rated output 4	
Rated current	16,3 A
Rated current 1	15,5 A
Rated current 2	16,3 A
Rated current 3	16,9 A
Rated current 4	
Fuse protection	20 A
Fuse protection 1	16 A
Fuse protection 2	20 A
Fuse protection 3	20 A
Fuse protection 4	
Frequency	50 Hz

Frequency 1	50/60 Hz
Frequency 2	50/60 Hz
Frequency 3	50/- Hz
Frequency 4	
Phases	2/PE
Conductivity σ15 ≤	909 µS/cm
Conductivity σ15 ≤ (at ϑcold ≤ 25 °C)	909 µS/cm
Conductivity σ15 ≤ (at ϑcold > 25 °C)	909 µS/cm
Resistivity ρ15 ≥	1100 Ω cm
Resistivity ρ15 ≥ (at ϑcold ≤ 25 °C)	1100 Ω cm
Resistivity ρ15 ≥ (at ϑcold > 25 °C)	1100 Ω cm
Height	143 mm
Width	190 mm
Depth	82 mm
Water connection	G 3/8 A
ON	>2,6 l/min
IP rating	IP25
Colour	white
Weight	1.40 kg
Energy efficiency class	A

Contact information

You have questions? We appreciate to help you:
Call **+49 5531 - 7020**
Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.