

EIL 3 Premium

PRODUCT-NO.: 200134

Compact convenience that speaks for itself Your preferred temperature without the annoyance of heat loss from the pipework along the way – this mini instantaneous water heater brings you the "new normal". The electronically controlled appliance is especially well suited to hand washbasins, where it will supply you with small amounts of warm water. Enjoy hot water without any detours This mini instantaneous water heater makes a convincing case for efficient DHW heating: since you connect the appliance directly to the tap and have the choice of installation above or below the washbasin, you save both water and energy. This is because there are no long pipe runs. There is no need to manually set the temperature either. This makes the appliance more practical and convenient for you to use.



The main features

Mini instantaneous water heater with electronic control for small amounts of hot water available immediately

Flexible installation thanks to undersink or oversink installation

Can be operated with pressure-tested or non-pressurised taps

Accurate temperature delivery up to the maximum output

Temperature limit adjustable between approx. 30 °C and 50 °C

Special aerator for perfect flow pattern

For straightforward electrical connection to any standard socket



Type	EIL 3 Premium	EIL 4 Premium	EIL 6 Premium
Part no.	200134	200135	200136

Technical data

Rated voltage	230 V	230 V	230 V
Rated voltage 1	200 V	200 V	200 V
Rated voltage 2	220 V	220 V	220 V
Rated voltage 3	230 V	230 V	230 V
Rated voltage 4	240 V	240 V	240 V
Rated output	3.53 kW	4.4 kW	5.7 kW
Rated output 1	2.7 kW	3.3 kW	4.3 kW
Rated output 2	3.2 kW	4.0 kW	5.2 kW
Rated output 3	3.53 kW	4.4 kW	5.7 kW
Rated output 4	3.8 kW	4.8 kW	6.2 kW
Rated current	15.2 A	19.1 A	24.7 A
Rated current 1	13.3 A	16.7 A	21.6 A
Rated current 2	14.5 A	18.2 A	23.6 A
Rated current 3	15.2 A	19.1 A	24.7 A
Rated current 4	15.8 A	20.0 A	25.8 A
Fuse protection	16 A	20 A	25 A
Fuse protection 1	16 A	20 A	25 A
Fuse protection 2	16 A	20 A	25 A
Fuse protection 3	16 A	20 A	25 A
Fuse protection 4	16 A	20 A	32 A
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 1	50/60 Hz	50/60 Hz	50/60 Hz

Frequency 2	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 3	50/60 Hz	50/60 Hz	50/60 Hz
Frequency 4	50/60 Hz	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE	1/N/PE
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^{\circ}\text{C}$)	1000 Ω cm	1000 Ω cm	1000 Ω cm
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ }^{\circ}\text{C}$)	1000 $\mu\text{S/cm}$	1000 $\mu\text{S/cm}$	1000 $\mu\text{S/cm}$
Height	143 mm	143 mm	143 mm
Width	190 mm	190 mm	190 mm
Depth	82 mm	82 mm	82 mm
ON	>1.5 l/min	>1.8 l/min	>2.2 l/min
IP rating	IP 25	IP 25	IP 25
Temperature setting	30 – 50 $^{\circ}\text{C}$	30 – 50 $^{\circ}\text{C}$	30 – 50 $^{\circ}\text{C}$
Colour	white	white	white
Weight	1.50 kg	1.50 kg	1.50 kg



Type	EIL 7 Premium
Part no.	200137
Technical data	
Rated voltage	400 V
Rated voltage 1	380 V
Rated voltage 2	400 V
Rated voltage 3	
Rated voltage 4	
Rated output	6.5 kW
Rated output 1	5.9 kW
Rated output 2	6.5 kW
Rated output 3	
Rated output 4	
Rated current	16.3 A
Rated current 1	15.5 A
Rated current 2	16.3 A
Rated current 3	
Rated current 4	
Fuse protection	20 A
Fuse protection 1	16 A
Fuse protection 2	20 A
Fuse protection 3	
Fuse protection 4	
Frequency	50/- Hz
Frequency 1	50/- Hz

Frequency 2	50/- Hz
Frequency 3	
Frequency 4	
Phases	2/PE
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25$ °C)	1000 Ω cm
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25$ °C)	1000 $\mu\text{S}/\text{cm}$
Height	143 mm
Width	190 mm
Depth	82 mm
ON	>2.2 l/min
IP rating	IP 25
Temperature setting	30 – 50 °C
Colour	white
Weight	1.50 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.