

# EIL 3 Trend + UT

PRODUCT-NO.: 200146

This set comprising a mini instantaneous water heater and twin lever tap ensures optimum compatibility between the appliance and the tap.

## The main features

For energy efficient and water-saving supply of one hand washbasin

Mini instantaneous water heater as a set with matching tap





Type	EIL 3 Trend + UT
Part no.	200146

## Technical data

Rated voltage	230 V
Rated voltage 1	200 V
Rated voltage 2	220 V
Rated voltage 3	230 V
Rated voltage 4	240 V
Rated output	3,53 kW
Rated output 1	2,7 kW
Rated output 2	3,2 kW
Rated output 3	3,53 kW
Rated output 4	3,8 kW
Rated current	15,2 A
Rated current 1	13,3 A
Rated current 2	14,5 A
Rated current 3	15,2 A
Rated current 4	15,8 A
Fuse protection	16 A
Fuse protection 1	16 A
Fuse protection 2	16 A
Fuse protection 3	16 A
Fuse protection 4	16 A
Frequency	50/60 Hz
Frequency 1	50/60 Hz

Frequency 2	50/60 Hz
Frequency 3	50/60 Hz
Frequency 4	50/60 Hz
Phases	1/N/PE
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ °C}$ )	1100 $\Omega$ cm
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} > 25 \text{ °C}$ )	1100 $\Omega$ cm
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25 \text{ °C}$ )	909 $\mu\text{S/cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} > 25 \text{ °C}$ )	909 $\mu\text{S/cm}$
Height	143 mm
Width	190 mm
Depth	82 mm
Water connection	G 3/8 A
ON	> 1,0 l/min
IP rating	IP 25
Colour	white
Weight	1.40 kg

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.