

EIL 6 Plus

MINI INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 200140

The main features

Undersink installation

Can be operated with pressurised and non-pressurised taps

Special aerator for perfect flow pattern





Type	EIL 3 Plus	EIL 4 Plus	EIL 6 Plus
Part no.	200138	200139	200140
Rated output	3,53 kW	4,4 kW	5,7 kW
Height	143 mm	143 mm	143 mm
Width	190 mm	190 mm	190 mm
Depth	82 mm	82 mm	82 mm

Technical data

Rated voltage 1	200 V	200 V	200 V
Rated output 1	2,7 kW	3,3 kW	4,3 kW
Rated current 1	13,3 A	16,7 A	21,6 A
Frequency 1	50/60 Hz	50/60 Hz	50/60 Hz
Fuse 1	16 A	20 A	25 A
Rated voltage 2	220 V	220 V	220 V
Rated output 2	3,2 kW	4,0 kW	5,2 kW
Rated current 2	14,5 A	18,2 A	23,6 A
Frequency 2	50/60 Hz	50/60 Hz	50/60 Hz
Fuse 2	16 A	20 A	25 A
Rated voltage 3	230 V	230 V	230 V
Rated output 3	3,53 kW	4,4 kW	5,7 kW
Rated current 3	15,2 A	19,1 A	24,7 A
Frequency 3	50/60 Hz	50/60 Hz	50/60 Hz
Fuse 3	16 A	20 A	25 A
Rated voltage 4	240 V	240 V	240 V
Rated output 4	3,8 kW	4,8 kW	6,2 kW
Rated current 4	15,8 A	20 A	25,8 A

Frequency 4	50/60 Hz	50/60 Hz	50/60 Hz
MCB/fuse 4	16 A	20 A	32 A
Phases	1/N/PE	1/N/PE	1/N/PE
Water connection	G 3/8 A	G 3/8 A	G 3/8 A
Specific resistance $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25$ °C)	1100 Ω cm	1100 Ω cm	1100 Ω cm
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25$ °C)	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$
Energy efficiency class	A	A	A
IP-Rating	IP25	IP25	IP25
Colour	white	white	white
Weight	1,4 kg	1,4 kg	1,4 kg



Type	EIL 7 Plus
Part no.	200141
Rated output	6,5 kW
Height	143 mm
Width	190 mm
Depth	82 mm

Technical data

Rated voltage 1	380 V
Rated output 1	5,9 kW
Rated current 1	15,5 A
Frequency 1	50/60 Hz
Fuse 1	16 A
Rated voltage 2	400 V
Rated output 2	6,5 kW
Rated current 2	16,3 A
Frequency 2	50/60 Hz
Fuse 2	20 A
Rated voltage 3	415 V
Rated output 3	7,0 kW
Rated current 3	16,9 A
Frequency 3	50/- Hz
Fuse 3	20 A
Rated voltage 4	
Rated output 4	
Rated current 4	

Frequency 4**MCB/fuse 4****Phases** 2/PE**Water connection** G 3/8 A**Specific resistance $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25$ °C)** 1100 Ω cm**Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25$ °C)** 909 $\mu\text{S}/\text{cm}$ **Energy efficiency class** A**IP-Rating** IP25**Colour** white**Weight** 1,4 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.