

EIL 3 Trend

MINI INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 200142

The main features

Operation with non-pressurised tap

Special aerator for perfect flow pattern





Type	EIL 3 Trend	EIL 4 Trend	EIL 6 Trend
Part no.	200142	200143	200144
Rated output	3,53 kW	4,4 kW	5,7 kW
Width	190 mm	190 mm	190 mm
Height	143 mm	143 mm	143 mm
Depth	82 mm	82 mm	82 mm

Technical data

Rated voltage 1	200 V	200 V	200 V
Rated output 1	2,7 kW	3,3 kW	4,3 kW
Rated current 1	13,3 A	16,7 A	21,6 A
Frequency 1	50/60 Hz	50/60 Hz	50/60 Hz
Fuse 1	16 A	20 A	25 A
Rated voltage 2	220 V	220 V	220 V
Rated output 2	3,2 kW	4,0 kW	5,2 kW
Rated current 2	14,5 A	18,2 A	23,6 A
Frequency 2	50/60 Hz	50/60 Hz	50/60 Hz
Fuse 2	16 A	20 A	25 A
Rated voltage 3	230 V	230 V	230 V
Rated output 3	3,53 kW	4,4 kW	5,7 kW
Rated current 3	15,2 A	19,1 A	24,7 A
Frequency 3	50/60 Hz	50/60 Hz	50/60 Hz
Fuse 3	16 A	20 A	25 A
Rated voltage 4	240 V	240 V	240 V
Rated output 4	3,8 kW	4,8 kW	6,2 kW
Rated current 4	15,8 A	20 A	25.8 A

Frequency 4	50/60 Hz	50/60 Hz	50/60 Hz
MCB/fuse 4	16 A	20 A	32 A
Phases	1/N/PE	1/N/PE	1/N/PE
Water connection	G 3/8 A	G 3/8 A	G 3/8 A
Specific resistance $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25$ °C)	1100 Ω cm	1100 Ω cm	1100 Ω cm
Specific conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25$ °C)	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$
IP-Rating	IP25	IP25	IP25
Colour	white	white	white
Weight	1,40 kg	1,40 kg	1,40 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.