

Tempra 36 Trend

TEMPRA TREND

PRODUCT-NO.: 239218

The main features

Electronic control for maximum energy efficiency and accurate temperature delivery

Backlit LCD

Temperature limit (childproofing)

Compact space saving design

Easy and quick installation

High quality - Made in Germany





| Type | Tempra 12 Trend | Tempra 15 Trend | Tempra 20 Trend |
|------------------------------------|-----------------|-----------------|-----------------|
| Part no. | 239213 | 239214 | 239215 |
| Height | 369 mm | 369 mm | 369 mm |
| Width | 420 mm | 420 mm | 420 mm |
| Depth | 117 mm | 117 mm | 117 mm |
| Technical data | | | |
| Rated voltage 1 | 208 V | 208 V | 208 V |
| Rated output 1 | 9 kW | 10,8 kW | 14,4 kW |
| Rated current 1 | 44 A | 2 x 26 A | 2 x 35 A |
| Fuse 1 | 50 A | 2 x 30 A | 2 x 35 A |
| Rated voltage 2 | 240 V | 240 V | 240 V |
| Rated output 2 | 12 kW | 14,4 kW | 19,2 kW |
| Rated current 2 | 50 A | 2 x 30 A | 2 x 40 A |
| Fuse 2 | 50 A | 2 x 30 A | 2 x 40 A |
| Frequency | 50/60 Hz | 50/60 Hz | 50/60 Hz |
| Power supply | 1/GRD | 2/GRD | 2/GRD |
| Available temperature range | Off, 20-60 °C | Off, 20-60 °C | Off, 20-60 °C |
| Colour | white | white | white |
| Weight | 6,1 kg | 7,3 kg | 7,3 kg |



| Type | Tempra 24 Trend | Tempra 29 Trend | Tempra 36 Trend |
|----------|-----------------|-----------------|-----------------|
| Part no. | 239216 | 239217 | 239218 |
| Height | 369 mm | 369 mm | 369 mm |
| Width | 420 mm | 420 mm | 420 mm |
| Depth | 117 mm | 117 mm | 117 mm |

Technical data

| | | | |
|-----------------------------|---------------|---------------|---------------|
| Rated voltage 1 | 208 V | 208 V | 208 V |
| Rated output 1 | 18 kW | 21,6 kW | 27 kW |
| Rated current 1 | 2 x 44 A | 3 x 35 A | 3 x 44 A |
| Fuse 1 | 2 x 50 A | 3 x 35 A | 3 x 50 A |
| Rated voltage 2 | 240 V | 240 V | 240 V |
| Rated output 2 | 24 kW | 28,8 kW | 36 kW |
| Rated current 2 | 2 x 50 A | 3 x 40 A | 3 x 50 A |
| Fuse 2 | 2 x 50 A | 3 x 40 A | 3 x 50 A |
| Frequency | 50/60 Hz | 50/60 Hz | 50/60 Hz |
| Power supply | 2/GRD | 3/GRD | 3/GRD |
| Available temperature range | Off, 20-60 °C | Off, 20-60 °C | Off, 20-60 °C |
| Colour | white | white | white |
| Weight | 7,3 kg | 8,6 kg | 8,6 kg |

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.