

BGC 6 kW 500 mm ET

ACCESSORIES

PRODUCT-NO.: 003769

Threaded immersion heater for sealed unvented heating and DHW heating systems. Stepless temperature adjustment from approx. 10 °C to 80 °C. The temperature can be limited to 45/60/80 °C. Integral temperature controller with high limit safety cut-out. Heating element and protective pipe material: copper; threaded connection: brass, thread G 1 1/2 with PTFE gasket.



The main features

For matching to individual usage scenarios

High hot water convenience thanks to powerful heating elements

Stepless temperature setting via rotary selector



Type	BGC 6 kW 500 mm ET	BGC/45
Part no.	003769	075115

Technical data

Connected load ~ 230 V	2-5,7 kW	2-5,7 kW
Connected load ~ 400 V	6 kW	6 kW
Power supply	1/N/PE, 2/PE, 3/PE	1/N/PE, 2/PE, 3/PE
Rated voltage	230/400 V	230/400 V
Frequency	50/60 Hz	50/60 Hz
Version	Universal flange	Universal flange
IP rating	IP 44	IP 44
Immersion depth	500 mm	455 mm

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.