

SB 402 S

FLOOR MOUNTED CYLINDER

Improve your home hot water supply Ingenious extras for more hot water

convenience To ensure that the heat is transferred to the water and not wasted, this floor mounted combi cylinder is equipped with high grade thermal insulation. The result for you is maximum hot water convenience in your home. In addition, this energy efficient appliance supplies several draw-off points at once.

The main features

Floor mounted cylinder for central DHW heating

Thermometer and signal anode with display element

Two flanged apertures for individual use of flanged immersion heaters

Highly effective thermal insulation included for low heat losses

Special enamel coating for a long service life

PRODUCT-NO.: 185355



SB 302 S

Product-No.: 185354



Type	SB 302 S	SB 402 S
Part no.	185354	185355

Technical data

Energy efficiency class	C	C
Nominal capacity	300 l	400 l
Colour	pure white/ basalt grey	pure white/ basalt grey
Number of flanged apertures	2	2
Water connection	G 1 A	G 1 A
Height	1585 mm	1755 mm
Width	700 mm	750 mm
Depth	700 mm	750 mm
Immersion depth	530 mm	580 mm
Weight, empty	101 kg	119 kg
Flange diameter	210 mm	210 mm

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.