





# SB 402 S





FLOORSTANDING CYLINDERS FROM 200 L

PRODUCT-NO.: 185355

## Obligatory supplies

Article	Part no.	Type	Description
	074374	SV 3/4-6	Diaphragm safety valve with brass casing, response pressure 0.6 Mpa (6 bar).
	074371	DMV / ZH 1	Special pressure reducing valve G 1 as supplement to ZH 1, if the static pressure at the installation location exceeds 0.48 MPa (4.8 bar). Brass. Connection 3/4 inch.
	074375	SV 3/4-10	Safety valve
	074370	ZH 1	Safety assembly ZH 1 for sealed unvented electric floorstanding cylinders pressure reducing valve DMV/ZH1, may be retrofitted. Brass casing, G 3/4 connections. Response pressure, safety relief valve: 0,6 MPa, Connection: G 1 A

## Additional supplies

Article	Part no.	Type	Description
	143498	Replacement anode <sup>3</sup> / <sub>4</sub>	Replacement link anode rod
	075115	BGC/45	Threaded immersion heater, Depth of insertion: 455 mm
	232030	BGC 2/60	Threaded immersion heater, Depth of insertion: 480 mm
	074370	ZH 1	Safety assembly ZH 1 for sealed unvented electric floorstanding cylinders pressure reducing valve DMV/ZH1, may be retrofitted. Brass casing, G

3/4 connections. Response pressure, safety relief valve: 0,6 MPa, Connection: G 1 A



076102

**B 21**

Blank flange, Flange diameter: 210 mm



071330

**FCR 21/60**

Flanged immersion heater, Connected load with ~ 230 V: 2-4 kW, Connected load with ~ 400 V: 2-6 kW, Version: Single/two line



074371

**DMV / ZH 1**

Special pressure reducing valve G 1 as supplement to ZH 1, if the static pressure at the installation location exceeds 0.48 MPa (4.8 bar). Brass. Connection 3/4 inch.

**Contact information**

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to [info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)

**Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.