





# SHO AC 600 6/12

FLOORSTANDING CYLINDERS FROM 200 L

PRODUCT-NO.: 003352

## Additional supplies

Article	Part no.	Type	Description
	074371	<b>DMV / ZH 1</b>	Special pressure reducing valve G 1 as supplement to ZH 1, if the static pressure at the installation location exceeds 0.48 MPa (4.8 bar). Brass. Connection 3/4 inch.
	236077	<b>WDS 600</b>	Height: 1850 mm, Thickness: 100 mm, Insulation for: SHO AC 600
	143499	<b>Replacement anode 1 1/4</b>	Replacement link anode rod
	074370	<b>ZH 1</b>	Safety assembly ZH 1 for sealed unvented electric floorstanding cylinders pressure reducing valve DMV/ZH1, may be retrofitted. Brass casing, G 3/4 connections. Response pressure, safety relief valve: 0,6 MPa, Connection: G 3/4 A

**Contact information**

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to [info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)

**Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.