





SHO AC 600 6/12




FLOORSTANDING CYLINDERS FROM 200 L

PRODUCT-NO.: 003352

Obligatory supplies

Article	Part no.	Type	Description
	074371	DMV / ZH 1	Special pressure reducing valve G 1 as supplement to ZH 1, if the static pressure at the installation location exceeds 0.48 MPa (4.8 bar). Brass. Connection 3/4 inch.
	074375	SV 3/4-10	Safety valve
	074374	SV 3/4-6	Diaphragm safety valve with brass casing, response pressure 0.6 Mpa (6 bar).
	074370	ZH 1	Safety assembly ZH 1 for sealed unvented electric floorstanding cylinders pressure reducing valve DMV/ZH1, may be retrofitted. Brass casing, G 3/4 connections. Response pressure, safety relief valve: 0,6 MPa, Connection: G 1 A

Additional supplies

Article	Part no.	Type	Description
	074371	DMV / ZH 1	Special pressure reducing valve G 1 as supplement to ZH 1, if the static pressure at the installation location exceeds 0.48 MPa (4.8 bar). Brass. Connection 3/4 inch.
	236077	WDS 600	Height: 1850 mm, Thickness: 100 mm
	143499	Replacement anode 1 1/4	Replacement link anode rod



074370

ZH 1

Safety assembly ZH 1 for sealed unvented electric floorstanding cylinders pressure reducing valve DMV/ZH1, may be retrofitted. Brass casing, G 3/4 connections. Response pressure, safety relief valve: 0,6 MPa, Connection: G 1 A

Contact information

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.