PRODUCT-NO.: 182120



SHW 200 S

FLOOR MOUNTED CYLINDER

Experience the stability of mature technology

It's never too late for hot water convenience. As demonstrated by our floor mounted cylinders, which can be retrofitted to upgrade your home. The thermometer, protective anode and variable cold water inlet pipe facilitate handling.



Powerful and quick to heat up

The powerful floor mounted cylinder supplies several draw-off points with ease and offers extra convenience in the form of the rapid heat-up button. The steel cylinder with special enamel coating shows just how well we harmonise technology and design – a perfect symbiosis for relaxation in your own four walls.



SHW 300 S

Product-No.: 182121



SHW 400 S

Product-No.: 182122

The main features

Floor mounted cylinder for central DHW heating

Simple temperature selection from 35-82 °C with variable adjustment on the appliance

Rapid heat-up button for demand-dependent heating

Cost savings possible if cheaper off-peak tariffs are used

Low standby energy consumption

Special enamel coating for a long service life









| Туре | SHW 200 S | SHW 300 S | SHW 400 S |
|----------|-----------|-----------|-----------|
| Part no. | 182120 | 182121 | 182122 |

Technical data

| Connected load ~ 230 V | 2-4 kW | 2-4 kW | 2-4 kW |
|--|----------------------------|----------------------------|----------------------------|
| Connected load ~ 400 V | 2-6 kW | 2-6 kW | 2-6 kW |
| Power supply | 1/N/PE, 3/N/PE | 1/N/PE, 3/N/PE | 1/N/PE, 3/N/P |
| Rated voltage | 230/400 V | 230/400 V | 230/400 V |
| Frequency | 50/60 Hz | 50/60 Hz | 50/60 Hz |
| Load profile | XL | XL | XL |
| Energy efficiency class | С | С | С |
| Standby energy consumption/24 h at 65 °C | 1.40 kWh | 1.80 kWh | 2.10 kWh |
| Nominal capacity | 200 l | 300 l | 400 l |
| Mixed water amount at 40 °C | 318 l | 447 | 639 l |
| Temperature setting range | 35-82 °C | 35-82 °C | 35-82 °C |
| Max. flow rate | 30 l/min | 38 l/min | 45 l/min |
| Max. permissible pressure | 0.60 MPa | 0.60 MPa | 0.60 MPa |
| Flanged immersion heater version | universal | universal | universal |
| Colour | pure white/ basalt grey | pure white/ basalt grey | pure white/ basalt grey |
| IP rating | IP24 | IP24 | IP24 |
| Water connection | G 1 A | G 1 A | G 1 A |
| Height | 1578 mm | 1593 mm | 1763 mm |
| W idth | 630 mm | 700 mm | 750 mm |
| Depth | 730 mm | 815 mm | 865 mm |



Weight, empty 65 kg 77 kg 90 kg



Contact information

You have questions? We appreciate to help you: Call +49 5531 - 7020 Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.