

SHW 300 ACE

FLOORSTANDING CYLINDERS FROM 200 L

PRODUCT-NO.: 070075

The sealed unvented floorstanding DHW cylinder SHW..ACE can hold 200, 300 or 400 litres of DHW, subject to model. The cylinder is sized for any number of draw-off points. The cylinder is made from steel with a special internal enamel coating, and is fitted with highly-effective insulation for optimum energy efficiency.



The main features

Cylinder with 200, 300, 400 litres (subject to model)

2.0 - 6.0 kW (subject to model and connection type)

Variable temperature selection from approx. 35 °C to 82 °C

Thermometer

Signal anode



Type	SHW 200 ACE	SHW 300 ACE	SHW 400 ACE
Part no.	070074	070075	070076
Rated capacity	200 l	300 l	400 l
Height	1578 mm	1593 mm	1763 mm
Width	550 mm	650 mm	700 mm
Depth	690 mm	790 mm	840 mm

Technical data

Connected load with ~ 230 V	2-6 kW	2-6 kW	2-6 kW
Connected load with ~ 400 V	4-6 kW	4-6 kW	4-6 kW
Power supply	1/N/PE, 3/N/PE	1/N/PE, 3/N/PE	1/N/PE, 3/N/PE
Rated voltage	230/400 V	230/400 V	230/400 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Water connection	G 1	G 1	G 1
Weight	54 kg	67 kg	85 kg
Standby power consumption/24 h	1,90 kWh	2,30 kWh	2,60 kWh
Colour	white	white	white
IP-Rating	IP25	IP25	IP25
Energy efficiency class	C	C	C

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.