

UFP 5 t Si

SMALL WATER HEATERS 5 TO 15 L

PRODUCT-NO.: 222176

The small water heaters for undersink installation make their case in many ways. They are equipped with a variable temperature selection from 35 °C and 85 °C, enabling water to be drawn at all times at the same temperature. The optional temperature limits at 38, 45, 55 or 65 °C act as anti-scalding settings or can be used as economy settings. With the SNU 5 SL anti-drip-comfort, the anti-drip function prevents the tap from dripping during heating up, which in turn prevents scale deposits and saves water. Furthermore, the Thermostop function prevent heat from being radiated via the mixer tap in standby when operating the SNU 5 SL anti-drip-comfort, SNU 10 SL comfort and the UFP 5 t.



The main features

Small water heater, 5 litre capacity

2 kW connected load

Undersink installation

Thermostop function

Low standby loss power consumption

Splashproof to IP 24 D

Plug-in unit for electrical connection to any standard socket

For a single draw-off point



Type	UFP 5 t Si
Part no.	222176
Connected load	2 kW
Height	418 mm
Width	252 mm
Depth	222 mm

Technical data

Rated voltage 1	220 V
Rated output 1	1,8 kW
Rated current 1	8,3 A
Fuse 1	10 A
Rated voltage 2	230 V
Rated output 2	2,0 kW
Rated current 2	8,7 A
Fuse 2	10 A
Rated voltage 3	240 V
Rated output 3	2,2 kW
Rated current 3	9,1 A
Fuse 3	10 A
Rated capacity	5 l
Frequency	50/60 Hz
Phases	1/N/PE
Power supply	1/N/PE
Standby power consumption/24 h	0,23 kWh
Colour	white

IP-Rating	IP24
Energy efficiency class	A
Weight	3,10 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.