

PSH 50 Classic

WALL MOUNTED CYLINDER

PRODUCT-NO.: 235960

Variable selection of your preferred temperature **Highly intuitive operation** A wall mounted cylinder for greater challenges: this model simultaneously supplies pleasantly hot water to multiple draw-off points in your home – for example, the bathroom and kitchen. Greater comfort and convenience for you all round.

The main features

Hydraulically controlled wall mounted cylinder

High grade thermal insulation

Variable temperature selection in the range of 30-70 °C

Temperature curve display for visual check of the water temperature

Frost protection integrated in the DHW cylinder



PSH 80 Classic

Product-No.: 235961



PSH 100 Classic

Product-No.: 235962



PSH 120 Classic

Product-No.: 235963



PSH 150 Classic

Product-No.: 235964



PSH 200 Classic

Product-No.: 235965



Type	PSH 50 Classic	PSH 80 Classic	PSH 100 Classic
Part no.	235960	235961	235962

Technical data

Connected load ~ 230 V	1.8 kW	1.8 kW	1.8 kW
Power supply	1/N/PE	1/N/PE	1/N/PE
Rated voltage	220-240 V	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Load profile	M	M	L
Energy efficiency class	C	C	C
Standby energy consumption/24 h at 65 °C	0.96 kWh	1.22 kWh	1.47 kWh
Nominal capacity	53 l	80 l	100 l
Mixed water amount at 40 °C	82 l	125 l	168 l
Temperature setting range	30-70 °C	30-70 °C	30-70 °C
Max. flow rate	23.5 l/min	23.5 l/min	23.5 l/min
Colour	white	white	white
IP rating	IP24	IP24	IP24
Height	609 mm	810 mm	964 mm
Width	475 mm	475 mm	475 mm
Depth	483 mm	483 mm	483 mm
Weight	19.00 kg	28.00 kg	33.00 kg



Type	PSH 120 Classic	PSH 150 Classic	PSH 200 Classic
Part no.	235963	235964	235965

Technical data

Connected load ~ 230 V	1.8 kW	1.8 kW	1.8 kW
Power supply	1/N/PE	1/N/PE	1/N/PE
Rated voltage	220-240 V	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Load profile	L	L	XL
Energy efficiency class	C	C	C
Standby energy consumption/24 h at 65 °C	1.73 kWh	2.05 kWh	2.45 kWh
Nominal capacity	120 l	150 l	192 l
Mixed water amount at 40 °C	219 l	270 l	347 l
Temperature setting range	30-70 °C	30-70 °C	30-70 °C
Max. flow rate	23.5 l/min	23.5 l/min	23.5 l/min
Colour	white	white	white
IP rating	IP24	IP24	IP24
Height	1117 mm	1349 mm	1704 mm
Width	475 mm	475 mm	475 mm
Depth	483 mm	483 mm	483 mm
Weight	39.00 kg	46.00 kg	56.00 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.