

# PSH-H 30 Trend

WALL MOUNTED CYLINDER

PRODUCT-NO.: 204770

**Comfort meets elegance** Wide choice of temperature settings Hot water is something you need many times over throughout the day. It is always available to you with this wall mounted cylinder. This is because the appliance is equipped with an automatic reheating function.

## The main features

Electronically controlled wall mounted cylinder

Compact, space saving installation thanks to horizontal design

Very low energy losses thanks to high grade thermal insulation

Long service life thanks to special enamel coating on the inside



**PSH-H 50 Trend**

Product-No.: 204771



**PSH-H 80 Trend**

Product-No.: 204772



**PSH-H 100 Trend**

Product-No.: 204773



**PSH-H 120 Trend**

Product-No.: 204774



**PSH-H 150 Trend**

Product-No.: 204775



**PSH-H 200 Trend**

Product-No.: 204776



Type	PSH-H 30 Trend	PSH-H 50 Trend	PSH-H 80 Trend
Part no.	204770	204771	204772

## Technical data

Connected load ~ 230 V	2 kW	2 kW	2 kW
Rated voltage	220-240 V	220-240 V	220-240 V
Load profile	S	M	M
Energy efficiency class	C	C	C
Standby energy consumption/24 h at 65 °C	0.78 kWh	1.09 kWh	1.04 kWh
Nominal capacity	30 l	50 l	80 l
Mixed water amount at 40 °C	46,1 l	70,5 l	108 l
Temperature setting range	30-80 °C	30-80 °C	30-80 °C
Max. flow rate	23,5 l/min	23,5 l/min	23,5 l/min
Colour	white	white	white
IP rating	IP25	IP25	IP25
Height	412 mm	412 mm	517 mm
Width	642 mm	897 mm	871 mm
Depth	419 mm	419 mm	545 mm
Weight	18.40 kg	23.40 kg	31.10 kg



Type	PSH-H 100 Trend	PSH-H 120 Trend	PSH-H 150 Trend
Part no.	204773	204774	204775

## Technical data

Connected load ~ 230 V	2 kW	2 kW	2 kW
Rated voltage	220-240 V	220-240 V	220-240 V
Load profile	M	L	L
Energy efficiency class	C	C	C
Standby energy consumption/24 h at 65 °C	1.20 kWh	1.41 kWh	1.61 kWh
Nominal capacity	100 l	120 l	150 l
Mixed water amount at 40 °C	137,3 l	128,3 l	159,4 l
Temperature setting range	30-80 °C	30-80 °C	30-80 °C
Max. flow rate	23,5 l/min	23,5 l/min	23,5 l/min
Colour	white	white	white
IP rating	IP25	IP25	IP25
Height	517 mm	517 mm	517 mm
Width	1025 mm	1178 mm	1410 mm
Depth	545 mm	545 mm	545 mm
Weight	35.10 kg	41.10 kg	48.40 kg



Type	PSH-H 200 Trend
Part no.	204776

### Technical data

Connected load ~ 230 V	2 kW
Rated voltage	220-240 V
Load profile	L
Energy efficiency class	C
Standby energy consumption/24 h at 65 °C	1.97 kWh
Nominal capacity	192 l
Mixed water amount at 40 °C	194 l
Temperature setting range	30-80 °C
Max. flow rate	23,5 l/min
Colour	white
IP rating	IP25
Height	517 mm
Width	1715 mm
Depth	545 mm
Weight	58.80 kg

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.