

# PSH 120 Trend

WALL MOUNTED CYLINDER

**Comfort meets elegance** Wide choice of temperature settings Hot water is something you need many times over throughout the day. It is always available to you with this wall mounted cylinder. This is because the appliance is equipped with an automatic reheating function.

## The main features

---

Hydraulically controlled wall mounted cylinder

---

Elegant, rounded design

---

Variable temperature selection in the range of 30-75 °C

---

Exceptionally high grade thermal insulation

---

Long service life thanks to special enamel coating on the inside

PRODUCT-NO.: 232084



**PSH 30 Trend**

Product-No.: 232080



**PSH 50 Trend**

Product-No.: 232081



**PSH 80 Trend**

Product-No.: 232082



**PSH 100 Trend**

Product-No.: 232083



**PSH 150 Trend**

Product-No.: 232085



**PSH 200 Trend**

Product-No.: 232086



Type	PSH 30 Trend	PSH 50 Trend	PSH 80 Trend
Part no.	232080	232081	232082

## Technical data

Connected load ~ 230 V	2 kW	2 kW	2 kW
Power supply	1/N/PE 220-240 V 50/60 Hz	1/N/PE 220-240 V 50/60 Hz	1/N/PE 220-240 V 50/60 Hz
Rated voltage	220-240 V	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Load profile	S	M	M
Energy efficiency class	C	C	C
Standby energy consumption/24 h at 65 °C	0.53 kWh	0.73 kWh	0.79 kWh
Nominal capacity	30 l	50 l	80 l
Mixed water amount at 40 °C	52 l	99 l	142 l
Temperature setting range	30-75 °C	30-75 °C	30-75 °C
Max. flow rate	23.5 l/min	23.5 l/min	23.5 l/min
Colour	white	white	white
IP rating	IP25	IP25	IP25
Height	642 mm	897 mm	871 mm
Width	405 mm	405 mm	510 mm
Depth	410 mm	410 mm	520 mm
Weight	16.40 kg	21.40 kg	28.20 kg



Type	PSH 100 Trend	PSH 120 Trend	PSH 150 Trend
Part no.	232083	232084	232085

## Technical data

Connected load ~ 230 V	2 kW	2 kW	2 kW
Power supply	1/N/PE 220-240 V 50/60 Hz	1/N/PE 220-240 V 50/60 Hz	1/N/PE 220-240 V 50/60 Hz
Rated voltage	220-240 V	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Load profile	L	L	L
Energy efficiency class	C	C	C
Standby energy consumption/24 h at 65 °C	0.98 kWh	1.15 kWh	1.33 kWh
Nominal capacity	100 l	120 l	150 l
Mixed water amount at 40 °C	186 l	224 l	288 l
Temperature setting range	30-75 °C	30-75 °C	30-75 °C
Max. flow rate	23.5 l/min	23.5 l/min	23.5 l/min
Colour	white	white	white
IP rating	IP25	IP25	IP25
Height	1025 mm	1178 mm	1410 mm
Width	510 mm	510 mm	510 mm
Depth	520 mm	520 mm	520 mm
Weight	33.60 kg	39.10 kg	46.20 kg



Type	PSH 200 Trend
Part no.	232086

### Technical data

Connected load ~ 230 V	2 kW
Power supply	1/N/PE 220-240 V 50/60 Hz
Rated voltage	220-240 V
Frequency	50/60 Hz
Load profile	XL
Energy efficiency class	C
Standby energy consumption/24 h at 65 °C	1.61 kWh
Nominal capacity	192 l
Mixed water amount at 40 °C	351 l
Temperature setting range	30-75 °C
Max. flow rate	23.5 l/min
Colour	white
IP rating	IP25
Height	1715 mm
Width	510 mm
Depth	520 mm
Weight	56.30 kg

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.