

PSH 150 Trend

WALL MOUNTED CYLINDER

Comfort meets elegance Wide choice of temperature settings Hot water is something you need many times over throughout the day. It is always available to you with this wall mounted cylinder. This is because the appliance is equipped with an automatic reheating function.

The main features

Hydraulically controlled wall mounted cylinder

Elegant, rounded design

Variable temperature selection in the range of 30-75 °C

Exceptionally high grade thermal insulation

Long service life thanks to special enamel coating on the inside

PRODUCT-NO.: 232085



PSH 30 Trend

Product-No.: 232080



PSH 50 Trend

Product-No.: 232081



PSH 80 Trend

Product-No.: 232082



PSH 100 Trend

Product-No.: 232083



PSH 120 Trend

Product-No.: 232084



PSH 200 Trend

Product-No.: 232086



Type	PSH 30 Trend	PSH 50 Trend	PSH 80 Trend
Part no.	232080	232081	232082

Technical data

Connected load ~ 230 V	2 kW	2 kW	2 kW
Power supply	1/N/PE 220-240 V 50/60 Hz	1/N/PE 220-240 V 50/60 Hz	1/N/PE 220-240 V 50/60 Hz
Rated voltage	220-240 V	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Load profile	S	M	M
Energy efficiency class	C	C	C
Standby energy consumption/24 h at 65 °C	0.53 kWh	0.73 kWh	0.79 kWh
Nominal capacity	30 l	50 l	80 l
Mixed water amount at 40 °C	52 l	99 l	142 l
Temperature setting range	30-75 °C	30-75 °C	30-75 °C
Max. flow rate	23.5 l/min	23.5 l/min	23.5 l/min
Colour	white	white	white
IP rating	IP25	IP25	IP25
Height	642 mm	897 mm	871 mm
Width	405 mm	405 mm	510 mm
Depth	410 mm	410 mm	520 mm
Weight	16.40 kg	21.40 kg	28.20 kg



Type	PSH 100 Trend	PSH 120 Trend	PSH 150 Trend
Part no.	232083	232084	232085

Technical data

Connected load ~ 230 V	2 kW	2 kW	2 kW
Power supply	1/N/PE 220-240 V 50/60 Hz	1/N/PE 220-240 V 50/60 Hz	1/N/PE 220-240 V 50/60 Hz
Rated voltage	220-240 V	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Load profile	L	L	L
Energy efficiency class	C	C	C
Standby energy consumption/24 h at 65 °C	0.98 kWh	1.15 kWh	1.33 kWh
Nominal capacity	100 l	120 l	150 l
Mixed water amount at 40 °C	186 l	224 l	288 l
Temperature setting range	30-75 °C	30-75 °C	30-75 °C
Max. flow rate	23.5 l/min	23.5 l/min	23.5 l/min
Colour	white	white	white
IP rating	IP25	IP25	IP25
Height	1025 mm	1178 mm	1410 mm
Width	510 mm	510 mm	510 mm
Depth	520 mm	520 mm	520 mm
Weight	33.60 kg	39.10 kg	46.20 kg



Type	PSB 200 Trend
Part no.	232086

Technical data

Connected load ~ 230 V	2 kW
Power supply	1/N/PE 220-240 V 50/60 Hz
Rated voltage	220-240 V
Frequency	50/60 Hz
Load profile	XL
Energy efficiency class	C
Standby energy consumption/24 h at 65 °C	1.61 kWh
Nominal capacity	192 l
Mixed water amount at 40 °C	351 l
Temperature setting range	30-75 °C
Max. flow rate	23.5 l/min
Colour	white
IP rating	IP25
Height	1715 mm
Width	510 mm
Depth	520 mm
Weight	56.30 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.