

PSH 80 Si

WALL MOUNTED CYLINDERS 30 TO 150 L

PRODUCT-NO.: 074480

The main features

Single circuit operation

Protective anode

Installation also in connection with plastic pipework systems (observe manufacturer's details)

Variable external temperature adjustment (PSH 30-50 Si)

Variable internal temperature adjustment (PSH 80-150 Si)

Replaceable copper immersion heater

Thermal insulation

Power cable for fixed power supply, approx. 1 m for 30-50 l; without cable for 80-150 l





Type	PSH 30 Si	PSH 50 Si	PSH 80 Si
Part no.	074478	074479	074480
Rated capacity	30 l	50 l	80 l
Height	623 mm	918 mm	770 mm
Diameter	338 mm	338 mm	505 mm
Weight	14,00 kg	17,00 kg	26,00 kg

Technical data

Connected load with ~ 230 V	2 kW	2 kW	2,2 kW
Phases	1/N/PE	1/N/PE	1/N/PE
Frequency	50/- Hz	50/- Hz	50/- Hz
Standby energy consumption/24 h at 65 °C	0,76 kWh	1,13 kWh	1,05 kWh
Single circuit operating mode	X	X	X
IP-Rating	IP25	IP25	IP25
Weight	14,00 kg	17,00 kg	26,00 kg
Colour	white/grey	white/grey	white/grey
Max. permissible pressure	0,60 MPa	0,60 MPa	0,60 MPa



Type	PSH 100 Si	PSH 120 Si	PSH 150 Si
Part no.	074481	074482	074483
Rated capacity	100 l	120 l	150 l
Height	885 mm	1015 mm	1210 mm
Diameter	505 mm	505 mm	513 mm
Weight	31,00 kg	34,00 kg	40,00 kg

Technical data

Connected load with ~ 230 V	2,2 kW	2,2 kW	2,2 kW
Phases	1/N/PE	1/N/PE	1/N/PE
Frequency	50/- Hz	50/- Hz	50/- Hz
Standby energy consumption/24 h at 65 °C	1,25 kWh	1,35 kWh	1,65 kWh
Single circuit operating mode	X	X	X
IP-Rating	IP25	IP25	IP25
Weight	31,00 kg	34,00 kg	40,00 kg
Colour	white/grey	white/grey	white/grey
Max. permissible pressure	0,60 MPa	0,60 MPa	0,60 MPa

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.