

## PSH 120 Classic

WALL MOUNTED CYLINDERS 30 TO 150 L

PRODUCT-NO.: 235963

### The main features

120 l wall mounted cylinder

---

High-grade thermal insulation

---

Safety valve included





Type	PSH 50 Classic	PSH 80 Classic	PSH 100 Classic
Part no.	235960	235961	235962
Connected load with ~ 230 V	1.8 kW	1.8 kW	1.8 kW
Rated capacity	53 l	80 l	100 l
Height	609 mm	810 mm	964 mm
Diameter	475 mm	475 mm	475 mm

## Technical data

Connected load with ~ 230 V	1.8 kW	1.8 kW	1.8 kW
Power supply	1/N/PE	1/N/PE	1/N/PE
Rated voltage	220-240 V	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Standby energy consumption/24 h at 65 °C	0,96 kWh	1,22 kWh	1,47 kWh
Energy efficiency class	C	C	C
Colour	white	white	white
IP-Rating	IP24	IP24	IP24
Weight (dry)	19 kg	24 kg	28 kg



Type	PSH 120 Classic	PSH 150 Classic	PSH 200 Classic
Part no.	235963	235964	235965
Connected load with ~ 230 V	1.8 kW	1.8 kW	1.8 kW
Rated capacity	120 l	150 l	192 l
Height	1117 mm	1349 mm	1704 mm
Diameter	475 mm	475 mm	475 mm

## Technical data

Connected load with ~ 230 V	1.8 kW	1.8 kW	1.8 kW
Power supply	1/N/PE	1/N/PE	1/N/PE
Rated voltage	220-240 V	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Standby energy consumption/24 h at 65 °C	1,73 kWh	2,05 kWh	2,45 kWh
Energy efficiency class	C	C	C
Colour	white	white	white
IP-Rating	IP24	IP24	IP24
Weight (dry)	32 kg	39 kg	50 kg

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.