

PSH 120 W-L

WALL MOUNTED CYLINDERS 30 TO 150 L

PRODUCT-NO.: 236244

The main features

High energy efficiency thanks to optimum thermal insulation

Heat exchanger connection for connecting to a heating system

DHW circulation connection increases DHW convenience in longer pipe networks

Temperature curve display on the outer jacket

Easy to transport and install with ergonomic recessed grips on the appliance

Wall mounting bracket for horizontal installation





Type	PSH 80 W-L	PSH 120 W-L	PSH 80 W-R
Part no.	236242	236244	236243
Rated capacity	81 l	119 l	81 l
Height	891 mm	1178 mm	891 mm
Diameter	510 mm	510 mm	510 mm

Technical data

Standby energy consumption/24 h at 65 °C	0,93 kWh	1,17 kWh	0,93 kWh
Energy efficiency class	B	B	B
Colour	white	white	white
IP-Rating	IP25	IP25	IP25
Weight (dry)	46 kg	57 kg	46 kg



Type	PSH 120 W-R
Part no.	236245
Rated capacity	119 l
Height	1178 mm
Diameter	510 mm

Technical data

Standby energy consumption/24 h at 65 °C	1,17 kWh
Energy efficiency class	B
Colour	white
IP-Rating	IP25
Weight (dry)	57 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.