

# PSH 200 WE-L

WALL MOUNTED CYLINDERS 30 TO 150 L

PRODUCT-NO.: 236236

## The main features

High energy efficiency thanks to minimal standby energy losses

Heat exchanger connection and electric heating element for individual DHW convenience

Durable, low-scaling stainless steel heating element

Temperature curve display on the outer jacket

Variable temperature selection from 5 - 80 °C for high level of convenience

Easy to transport and install with ergonomic recessed grips on the appliance

Universal wall mounting bracket for quick and easy installation

DHW circulation connection increases DHW convenience in longer pipe networks





Type	PSH 80 WE-H	PSH 120 WE-H	PSH 150 WE-H
<b>Part no.</b>	236238	236239	236240
<b>Rated capacity</b>	79 l	120 l	151 l
<b>Height</b>			
<b>Diameter</b>	510 mm	510 mm	510 mm
<b>Technical data</b>			
<b>Connected load with ~ 230 V</b>	2 kW	2 kW	2 kW
<b>Rated voltage</b>	220-240 V	220-240 V	220-240 V
<b>Frequency</b>	50/60 Hz	50/60 Hz	50/60 Hz
<b>Phases</b>	1/N/PE	1/N/PE	1/N/PE
<b>Standby energy consumption/24 h at 65 °C</b>	1,04 kWh	1,41 kWh	1,81 kWh
<b>Energy efficiency class</b>	C	C	C
<b>Colour</b>	white	white	white
<b>IP-Rating</b>	IP25	IP25	IP25
<b>Weight (dry)</b>	42,2 kg	54,1 kg	61,2 kg



Type	PSH 200 WE-H	PSH 80 WE-L	PSH 120 WE-L
Part no.	236241	236230	236232
Rated capacity	191 l	79 l	120 l
Height		871 mm	1178 mm
Diameter	510 mm	510 mm	510 mm

## Technical data

Connected load with ~ 230 V	2 kW	2 kW	2 kW
Rated voltage	220-240 V	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE	1/N/PE
Standby energy consumption/24 h at 65 °C	1,67 kWh	0,93 kWh	1,17 kWh
Energy efficiency class	C	B	B
Colour	white	white	white
IP-Rating	IP25	IP25	IP25
Weight (dry)	72,5 kg	37,2 kg	48,1 kg



Type	PSH 150 WE-L	PSH 200 WE-L	PSH 80 WE-R
Part no.	236234	236236	236231
Rated capacity	151 l	191 l	79 l
Height	1410 mm	1715 mm	871 mm
Diameter	510 mm	510 mm	510 mm

## Technical data

Connected load with ~ 230 V	2 kW	2 kW	2 kW
Rated voltage	220-240 V	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE	1/N/PE
Standby energy consumption/24 h at 65 °C	1,49 kWh	1,71 kWh	0,93 kWh
Energy efficiency class	C	C	B
Colour	white	white	white
IP-Rating	IP25	IP25	IP25
Weight (dry)	55,2 kg	65,3 kg	37,2 kg



Type	PSH 120 WE-R	PSH 150 WE-R	PSH 200 WE-R
Part no.	236233	236235	236237
Rated capacity	120 l	151 l	191 l
Height	1178 mm	1410 mm	1715 mm
Diameter	510 mm	510 mm	510 mm

## Technical data

Connected load with ~ 230 V	2 kW	2 kW	2 kW
Rated voltage	220-240 V	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE	1/N/PE
Standby energy consumption/24 h at 65 °C	1,17 kWh	1,49 kWh	1,71 kWh
Energy efficiency class	B	C	C
Colour	white	white	white
IP-Rating	IP25	IP25	IP25
Weight (dry)	48,1 kg	55,2 kg	65,3 kg

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.