

SH 150 S electronic

WALL MOUNTED CYLINDER

PRODUCT-NO.: 073052

Convenient and accurate control of your hot water

Your wish is this wall mounted cylinder's command. It features high grade thermal insulation, meaning only a minimal amount of energy is lost in operation. To facilitate effortless temperature settings, we have integrated an easy to use control element. An LED indicator shows you the amount of heat currently stored. This give you the optimum overview and more moments to relax.

The main features

Hydraulically controlled wall mounted cylinder

Electronic heat content indicator via LEDs

Simple temperature selection from 35-82 °C with variable adjustment on the appliance

Temperature limit possible

Special enamel coating for a long service life



SH 30 S electronic

Product-No.: 073047



SH 50 S electronic

Product-No.: 073048



SH 80 S electronic

Product-No.: 073049



SH 100 S electronic

Product-No.: 073050



SH 120 S electronic

Product-No.: 073051



Type	SH 30 S electronic	SH 50 S electronic	SH 80 S electronic
Part no.	073047	073048	073049

Technical data

Connected load ~ 230 V	1-4 kW	1-4 kW	1-4 kW
Connected load ~ 400 V	3-6 kW	3-6 kW	3-6 kW
Power supply	1/N/PE, 2/N/PE, 3/N/PE	1/N/PE, 2/N/PE, 3/N/PE	1/N/PE, 2/N/PE, 3/N/PE
Rated voltage	230/400 V	230/400 V	230/400 V
Frequency	50 Hz	50 Hz	50 Hz
Load profile	S	M	M
Energy efficiency class (A+ → F)	B	C	C
Standby energy consumption/24 h at 65 °C	0.46 kWh	0.54 kWh	0.67 kWh
Nominal capacity	30 l	50 l	80 l
Mixed water amount at 40 °C	50 l	80 l	122 l
Temperature setting range	35-82 °C	35-82 °C	35-82 °C
Max. flow rate	18 l/min	18 l/min	18 l/min
Colour	white	white	white
IP rating	IP25	IP25	IP25
Height	770 mm	740 mm	1050 mm
Width	410 mm	510 mm	510 mm
Depth	420 mm	510 mm	510 mm
Weight	23.10 kg	28.00 kg	38.00 kg



Type	SH 100 S electronic	SH 120 S electronic	SH 150 S electronic
Part no.	073050	073051	073052

Technical data

Connected load ~ 230 V	1-4 kW	1-4 kW	1-4 kW
Connected load ~ 400 V	3-6 kW	3-6 kW	3-6 kW
Power supply	1/N/PE, 2/N/PE, 3/N/PE	1/N/PE, 2/N/PE, 3/N/PE	1/N/PE, 2/N/PE, 3/N/PE
Rated voltage	230/400 V	230/400 V	230/400 V
Frequency	50 Hz	50 Hz	50 Hz
Load profile	L	L	XL
Energy efficiency class (A+ → F)	C	C	C
Standby energy consumption/24 h at 65 °C	0.86 kWh	0.99 kWh	1.10 kWh
Nominal capacity	100 l	120 l	150 l
Mixed water amount at 40 °C	133 l	182 l	229 l
Temperature setting range	35-82 °C	35-82 °C	35-82 °C
Max. flow rate	18 l/min	18 l/min	18 l/min
Colour	white	white	white
IP rating	IP25	IP25	IP25
Height	1050 mm	1210 mm	1445 mm
Width	510 mm	510 mm	510 mm
Depth	510 mm	510 mm	510 mm
Weight	40.80 kg	45.50 kg	53.30 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.