

SHD 100 S

WALL MOUNTED CYLINDERS 30 TO 150 L

PRODUCT-NO.: 073060

The SHD instantaneous DHW cylinder also offers commercial organisations a powerful alternative. It offers variable temperature selection up to 85 °C, and can supply hot water to several draw-off points. The SHD can be operated in three modes: As an instantaneous DHW cylinder, as a dual-circuit cylinder or as a single circuit cylinder, which also allows the use of pre-heated water (up to 75 °C).



The main features

100 l wall mounted cylinder

21 kW in instantaneous DHW cylinder mode

Variable temperature selection from approx. 35 °C to 82 °C

Standby power consumption 0.86 kWh per day

Heat-up display in the user interface

Quick and easy installation using mounting bracket and drilling template



Type	SHD 30 S	SHD 100 S
Part no.	073059	073060
Rated capacity	30 l	100 l
Height	770 mm	1050 mm
Width	410 mm	510 mm
Depth	420 mm	510 mm

Technical data

Connected load with ~ 400 V	3,4/20,4 kW	3,4/20,4 kW
Power supply	3/PE	3/PE
Rated voltage	400 V	400 V
Frequency	50 Hz	50 Hz
Standby power consumption/24 h	0,46 kWh	0,86 kWh
Colour	white	white
IP-Rating	IP25	IP25
Energy efficiency class	B	C
Weight	24,30 kg	40,10 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.