

EIL 3 Trend + OT

MINI INSTANTANEOUS WATER HEATERS

PRODUCT-NO.: 205971

This set comprising a mini instantaneous water heater and twin lever wall mounted tap ensures optimum compatibility between the appliance and the tap.

The main features

For energy efficient and water-saving supply of one hand washbasin

Mini instantaneous water heater as a set with matching tap



EIL 4 Trend + OT

Product-No.: 205974

Set-Components 1



Type	EIL 3 Trend	EIL 4 Trend
Product set	EIL 3 Trend + OT	EIL 4 Trend + OT

Technical data

Rated voltage	230 V	230 V
Rated voltage 1	200 V	200 V
Rated voltage 2	220 V	220 V
Rated voltage 3	230 V	230 V
Rated voltage 4	240 V	240 V
Rated output	3,53 kW	4,4 kW
Rated output 1	2,7 kW	3,3 kW
Rated output 2	3,2 kW	4,0 kW
Rated output 3	3,53 kW	4,4 kW
Rated output 4	3,8 kW	4,8 kW
Rated current	15,2 A	19,1 A
Rated current 1	13,3 A	16,7 A
Rated current 2	14,5 A	18,2 A
Rated current 3	15,2 A	19,1 A
Rated current 4	15,8 A	20 A
Fuse protection	16 A	20 A
Fuse protection 1	16 A	20 A
Fuse protection 2	16 A	20 A
Fuse protection 3	16 A	20 A

Fuse protection 4	16 A	20 A
Frequency	50/60 Hz	50/60 Hz
Frequency 1	50/60 Hz	50/60 Hz
Frequency 2	50/60 Hz	50/60 Hz
Frequency 3	50/60 Hz	50/60 Hz
Frequency 4	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE
Conductivity $\sigma_{15} \leq$	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} \leq 25\text{ }^{\circ}\text{C}$)	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$
Conductivity $\sigma_{15} \leq$ (at $\vartheta_{\text{cold}} > 25\text{ }^{\circ}\text{C}$)	909 $\mu\text{S}/\text{cm}$	909 $\mu\text{S}/\text{cm}$
Resistivity $\rho_{15} \geq$	1100 $\Omega\text{ cm}$	1100 $\Omega\text{ cm}$
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} \leq 25\text{ }^{\circ}\text{C}$)	1100 $\Omega\text{ cm}$	1100 $\Omega\text{ cm}$
Resistivity $\rho_{15} \geq$ (at $\vartheta_{\text{cold}} > 25\text{ }^{\circ}\text{C}$)	1100 $\Omega\text{ cm}$	1100 $\Omega\text{ cm}$
Height	143 mm	143 mm
Width	190 mm	190 mm
Depth	82 mm	82 mm
Water connection	G 3/8 A	G 3/8 A
Switch-on water flow rate	> 1,0 l/min	> 1.3 l/min
IP rating	IP25	IP25
Colour	white	white
Weight	1.40 kg	1.40 kg

Set-Components **2**



Type	MAW	MAW
Product set	EIL 3 Trend + OT	EIL 4 Trend + OT

Technical data

Application	Washbasin	Washbasin
Installation type	Wall mounted mixer tap	Wall mounted mixer tap
Surface	chrome plated	chrome plated
Connection	3/8 inch	3/8 inch
Cold water connection	1/2 inch	1/2 inch
Spout reach	157 mm	157 mm
Flow rate	5.2 l/min	5.2 l/min

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.