

# UPF 30/1-8 E

ACCESSORIES

PRODUCT-NO.: 232532

Energy efficient brine circuit pump (EEI  $\leq$  0.23), electronic control, with vapour diffusion-proof thermal insulation.

## The main features

Suitable for ground source heat pumps

UPF 30/1-8 E with 1500 mm connecting cable and non-return valve

Circulation pump with energy efficiency rating A





Type	UPF 30/1-8 E	UPF 30/1-12 E	UPF 40/1-8 E
Part no.	232532	235053	227413

## Technical data

Energy Efficiency Index EEI	0,23	0,23	0,23
Power consumption	8-130 W	16-310 W	12-310 W
Fitted length (gauge)	180 mm	180 mm	220 mm
Connection	G 2	G 2	DN 40
Head	8 m	12 m	8 m
Max. throughput	8 m <sup>3</sup> /h	10 m <sup>3</sup> /h	15 m <sup>3</sup> /h
Rated voltage	230 V	230 V	230 V



Type	UPF 50/1-12 E
Part no.	227414
Technical data	
Energy Efficiency Index EEI	0,23
Power consumption	25-590 W
Fitted length (gauge)	280 mm
Connection	DN 50
Head	12 m
Max. throughput	29 m <sup>3</sup> /h
Rated voltage	230 V

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.