

## UP 25/1-8 PCV


ACCESSORIES

PRODUCT-NO.: 235950

### The main features

UP 25/7.5 PCV, UP 25/1-8 PCV and UP 30/1-8 PCV with 1500 mm connecting cable

Circulation pump with energy efficiency category A





|          |             |              |               |
|----------|-------------|--------------|---------------|
| Type     | UP 40/1-8 E | UP 50/1-12 E | UP 25/1-8 PCV |
| Part no. | 227422      | 227423       | 235950        |

## Technical data

|   |                      |                      |                     |
|---|----------------------|----------------------|---------------------|
| Energy Efficiency Index EEI                 | 0,23                 | 0,23                 | 0,23                |
| Power consumption                           | 12-310 W             | 25-590 W             | 8-130 W             |
| Rated voltage                               | 230 V                | 230 V                | 230 V               |
| Fitted length (gauge)                       | 220 mm               | 280 mm               | 180 mm              |
| Connection                                  | DN 40                | DN 50                | G 1 1/2             |
| Head  | 8 m                  | 12 m                 | 8 m                 |
| Max. throughput                             | 15 m <sup>3</sup> /h | 29 m <sup>3</sup> /h | 8 m <sup>3</sup> /h |
| Controlled via differential pressure        | x                    | x                    | x                   |
| Control via PWM signal                      | -                    | -                    | x                   |
| Controlled via 0-10 V signal with IF module | x                    | x                    | -                   |



|      |               |
|------|---------------|
| Type | UP 30/1-8 PCV |
|------|---------------|

|          |        |
|----------|--------|
| Part no. | 235951 |
|----------|--------|

#### Technical data

|                             |      |
|-----------------------------|------|
| Energy Efficiency Index EEI | 0,23 |
|-----------------------------|------|

|                   |         |
|-------------------|---------|
| Power consumption | 8-130 W |
|-------------------|---------|

|               |       |
|---------------|-------|
| Rated voltage | 230 V |
|---------------|-------|

|                       |        |
|-----------------------|--------|
| Fitted length (gauge) | 180 mm |
|-----------------------|--------|

|            |     |
|------------|-----|
| Connection | G 2 |
|------------|-----|

|      |     |
|------|-----|
| Head | 8 m |
|------|-----|

|                 |                     |
|-----------------|---------------------|
| Max. throughput | 8 m <sup>3</sup> /h |
|-----------------|---------------------|

|                                      |   |
|--------------------------------------|---|
| Controlled via differential pressure | x |
|--------------------------------------|---|

|                        |   |
|------------------------|---|
| Control via PWM signal | x |
|------------------------|---|

|   |   |
|---|---|
| Controlled via 0-10 V signal with IF module | - |
|---|---|

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.